



Cisco

Exam Questions 300-610

Designing Cisco Data Center Infrastructure (DCID)

NEW QUESTION 1

What influences the number of ISLs that are required between Cisco MDS Series switches?

- A. FCoE protocol
- B. type of storage
- C. end-to-end oversubscription ratio
- D. N Port virtualization

Answer: C

NEW QUESTION 2

Which feature provides a sandbox to convert NX-OS CLI commands to REST-based scripts on Cisco Nexus 7700 Series Switches?

- A. NX-API
- B. Postman
- C. Bash shell
- D. Guest shell

Answer: A

NEW QUESTION 3

A failure occurs on the network between two BFD and OSPF neighbors. Drag and drop the protocol actions from the left into the correct order on the right.

BFD notifies the local OSPF process that the BFD neighbor is no longer reachable.	step 1
If an alternate path is available, routers immediately start converging on it.	Step 2
The BFD neighboring session with the OSPF peer is terminated.	Step 3
The local OSPF process tears down the OSPF neighbor relationship.	Step 4

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

BFD notifies the local OSPF process that the BFD neighbor is no longer reachable.	The BFD neighboring session with the OSPF peer is terminated.
If an alternate path is available, routers immediately start converging on it.	BFD notifies the local OSPF process that the BFD neighbor is no longer reachable.
The BFD neighboring session with the OSPF peer is terminated.	The local OSPF process tears down the OSPF neighbor relationship.
The local OSPF process tears down the OSPF neighbor relationship.	If an alternate path is available, routers immediately start converging on it.

NEW QUESTION 4

Which orchestration tool provides a graphical interface to manage LAN and SAN fabrics?

- A. Cisco Virtual Topology System

- B. Cisco Data Center Network Manager
- C. Cisco Nexus Fabric Manager
- D. Cisco CloudCenter

Answer: B

NEW QUESTION 5

Which mode must be enabled on a Cisco UCS Fabric Interconnect to connect directly to a storage array?

- A. NPIV mode
- B. FC end-host mode
- C. NPV mode
- D. FC switching mode

Answer: D

Explanation:

Section: Storage Network Design

NEW QUESTION 6

Drag and drop the configurations from the left onto the correct policies on the right.

Set the number of queues.

Set the RSS hash value.

Assign each vCon to a physical adapter.

Assign adapter order.

vNIC/vHBA Placement Policy

Ethernet Adapter Policy

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Set the number of queues.

Set the RSS hash value.

Assign each vCon to a physical adapter.

Assign adapter order.

vNIC/vHBA Placement Policy

Assign each vCon to a physical adapter.

Assign adapter order.

Ethernet Adapter Policy

Set the number of queues.

Set the RSS hash value.

NEW QUESTION 7

What are two reasons to select OTV as the DCI solution to connect multisite topologies? (Choose two.)

- A. It propagates hosts reachability without support of traffic flooding.
- B. Layer 3 failures do not propagate beyond the OTV edge device.
- C. It extends the spanning tree between data centers.
- D. It is an open standard.
- E. It constrains HSRP hello messages to each data center.

Answer: BC

NEW QUESTION 8

Which address pool is used when a vHBA template is created?

- A. MAC
- B. WWPN
- C. IP
- D. UUID

Answer: B

NEW QUESTION 9

Which approach splits a pair of clustered fabric interconnects into two standalone devices?

- A. Run the disable fips-mode command on each fabric interconnect.
- B. Run the connect local-management command on each fabric interconnect.
- C. Erase the configuration of both fabric interconnects.
- D. Unplug the Layer 1 and Layer 2 interfaces between the devices.

Answer: D

NEW QUESTION 10

Which Cisco HyperFlex feature provides virtual machine-level cost scaling for desktop virtualization growth?

- A. HyperFlex Edge support
- B. encryption offload cards
- C. dedicated compute nodes
- D. fabric interconnects

Answer: A

NEW QUESTION 10


Which two configurations are available by using a service profile template in Cisco UCS Manager? (Choose two.)

- A. number of vHBAs
- B. ARP entries
- C. UUID assignment
- D. VXLAN membership
- E. target server

Answer: AC

NEW QUESTION 13

Refer to the exhibit.




A Cisco UCS chassis that has two IOMs is discovered. The chassis discovery policy creates a fabric port channel. What is the result of this policy?

- A. Cisco UCS Manager creates two separate fabric port channels.
- B. Cisco UCS Manager creates a single fabric port channel.
- C. The port channel is disabled until an administrator enables it manually.
- D. Each uplink that connects an IOM is configured as a discrete link.

Answer: A

NEW QUESTION 14

Refer to the exhibit.



An engineer must assign multiple Fibre Channel IDs to a single port channel. Which two features must be enabled this goal? (Choose two.)

- A. SAN Pin Groups on the Cisco UCS Fabric Interconnects.
- B. NPV feature on the Cisco MDS Series.
- C. end-host mode feature on the Cisco UCS Fabric Interconnects
- D. NPIV feature on the Cisco MDS Series
- E. Smart Zoning feature on the Cisco UCS Fabric Interconnects

Answer: BD

NEW QUESTION 19

Which orchestration tool should be used for the management and analytics of servers across multiple sites?

- A. Cisco Intersight
- B. Cisco Nexus Fabric Manager

- C. Cisco UCS Manager
- D. Cisco Data Center Network Manager

Answer: A

NEW QUESTION 20

Which two methods mitigate congestion in a SAN network? (Choose two.)

- A. Configure ER_RDY to allow splitting of each ISL between switches into separate virtual links.
- B. Use the port-monitor command to detect slow drain devices.
- C. Configure the port channel to enable individual buffer-to-buffer credits.
- D. Configure the port monitor to allow categorization of a specific device as slow.
- E. Configure the flow control for the FC to use R_RDY.

Answer: BD

NEW QUESTION 21

Which factor determines the choice of platform designing a Cisco HyperFlex infrastructure to support computer-aided design applications?

- A. network speed
- B. GPU support
- C. storage capacity
- D. processor count

Answer: C

NEW QUESTION 24

Which two vSphere features must be included in the design of a Cisco HyperFlex systems stretched cluster? (Choose two.)

- A. HA
- B. VSS
- C. FT
- D. VDP
- E. DRS

Answer: AE

NEW QUESTION 29

Which authentication software natively runs within the CLI of Cisco NX-OS devices?

- A. Python
- B. Ansible
- C. Puppet
- D. Chef

Answer: B

NEW QUESTION 34

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

300-610 Practice Exam Features:

- * 300-610 Questions and Answers Updated Frequently
- * 300-610 Practice Questions Verified by Expert Senior Certified Staff
- * 300-610 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * 300-610 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The 300-610 Practice Test Here](#)