

# Exam Questions AWS-Certified-Developer-Associate

Amazon AWS Certified Developer - Associate

<https://www.2passeasy.com/dumps/AWS-Certified-Developer-Associate/>



### NEW QUESTION 1

A company needs to deploy all its cloud resources by using AWS CloudFormation templates. A developer must create an Amazon Simple Notification Service (Amazon SNS) automatic notification to help enforce this rule. The developer creates an SNS topic and subscribes the email address of the company's security team to the SNS topic.

The security team must receive a notification immediately if an IAM role is created without the use of CloudFormation.

Which solution will meet this requirement?

- A. Create an AWS Lambda function to filter events from CloudTrail if a role was created without CloudFormation. Configure the Lambda function to publish to the SNS topic.
- B. Create an Amazon EventBridge schedule to invoke the Lambda function every 15 minutes.
- C. Create an AWS Fargate task in Amazon Elastic Container Service (Amazon ECS) to filter events from CloudTrail if a role was created without CloudFormation. Configure the Fargate task to publish to the SNS topic. Create an Amazon EventBridge schedule to run the Fargate task every 15 minutes.
- D. Launch an Amazon EC2 instance that includes a script to filter events from CloudTrail if a role was created without CloudFormation. Configure the script to publish to the SNS topic.
- E. Configure the script to publish to the SNS topic.
- F. Create a cron job to run the script on the EC2 instance every 15 minutes.
- G. Create an Amazon EventBridge rule to filter events from CloudTrail if a role was created without CloudFormation. Specify the SNS topic as the target of the EventBridge rule.

**Answer:** D

#### Explanation:

Creating an Amazon EventBridge rule is the most efficient and scalable way to monitor and react to events from CloudTrail, such as the creation of an IAM role without CloudFormation. EventBridge allows you to specify a filter pattern to match the events you are interested in, and then specify an SNS topic as the target to send notifications. This solution does not require any additional resources or code, and it can trigger notifications in near real-time. The other solutions involve creating and managing additional resources, such as Lambda functions, Fargate tasks, or EC2 instances, and they rely on polling CloudTrail events every 15 minutes, which can introduce delays and increase costs. References

- ? Using Amazon EventBridge rules to process AWS CloudTrail events
- ? Using AWS CloudFormation to create and manage AWS Batch resources
- ? How to use AWS CloudFormation to configure auto scaling for Amazon Cognito and AWS AppSync
- ? Using AWS CloudFormation to automate the creation of AWS WAF web ACLs, rules, and conditions

### NEW QUESTION 2

An application that runs on AWS receives messages from an Amazon Simple Queue Service (Amazon SQS) queue and processes the messages in batches. The application sends the data to another SQS queue to be consumed by another legacy application. The legacy system can take up to 5 minutes to process some transaction data.

A developer wants to ensure that there are no out-of-order updates in the legacy system. The developer cannot alter the behavior of the legacy system.

Which solution will meet these requirements?

- A. Use an SQS FIFO queue.
- B. Configure the visibility timeout value.
- C. Use an SQS standard queue with a `SendMessageBatchRequestEntry` data type.
- D. Configure the `DelaySeconds` values.
- E. Use an SQS standard queue with a `SendMessageBatchRequestEntry` data type.
- F. Configure the visibility timeout value.
- G. Use an SQS FIFO queue.
- H. Configure the `DelaySeconds` value.

**Answer:** A

#### Explanation:

? An SQS FIFO queue is a type of queue that preserves the order of messages and ensures that each message is delivered and processed only once<sup>1</sup>. This is suitable for the scenario where the developer wants to ensure that there are no out-of-order updates in the legacy system.

? The visibility timeout value is the amount of time that a message is invisible in the queue after a consumer receives it<sup>2</sup>. This prevents other consumers from processing the same message simultaneously. If the consumer does not delete the message before the visibility timeout expires, the message becomes visible again and another consumer can receive it<sup>2</sup>.

? In this scenario, the developer needs to configure the visibility timeout value to be longer than the maximum processing time of the legacy system, which is 5 minutes. This will ensure that the message remains invisible in the queue until the legacy system finishes processing it and deletes it. This will prevent duplicate or out-of-order processing of messages by the legacy system.

### NEW QUESTION 3

A developer is creating an AWS Lambda function that needs credentials to connect to an Amazon RDS for MySQL database. An Amazon S3 bucket currently stores the credentials. The developer needs to improve the existing solution by implementing credential rotation and secure storage. The developer also needs to provide integration with the Lambda function.

Which solution should the developer use to store and retrieve the credentials with the LEAST management overhead?

- A. Store the credentials in AWS Systems Manager Parameter Store.
- B. Select the database that the parameter will access.
- C. Use the default AWS Key Management Service (AWS KMS) key to encrypt the parameter.
- D. Enable automatic rotation for the parameter.
- E. Use the parameter from Parameter Store on the Lambda function to connect to the database.
- F. Encrypt the credentials with the default AWS Key Management Service (AWS KMS) key.
- G. Store the credentials as environment variables for the Lambda function.
- H. Create a second Lambda function to generate new credentials and to rotate the credentials by updating the environment variables of the first Lambda function.
- I. Invoke the second Lambda function by using an Amazon EventBridge rule that runs on a schedule.
- J. Update the database to use the new credential.
- K. On the first Lambda function, retrieve the credentials from the environment variable.
- L. Decrypt the credentials by using AWS KMS. Connect to the database.

- M. Store the credentials in AWS Secrets Manager
- N. Set the secret type to Credentials for Amazon RDS database
- O. Select the database that the secret will access
- P. Use the default AWS Key Management Service (AWS KMS) key to encrypt the secret
- Q. Enable automatic rotation for the secret
- R. Use the secret from Secrets Manager on the Lambda function to connect to the database.
- S. Encrypt the credentials by using AWS Key Management Service (AWS KMS). Store the credentials in an Amazon DynamoDB table
- T. Create a second Lambda function to rotate the credential
- . Invoke the second Lambda function by using an Amazon EventBridge rule that runs on a schedule
- . Update the DynamoDB table
- . Update the database to use the generated credential
- . Retrieve the credentials from DynamoDB with the first Lambda function
- . Connect to the database.

**Answer: C**

**Explanation:**

AWS Secrets Manager is a service that helps you protect secrets needed to access your applications, services, and IT resources. Secrets Manager enables you to store, retrieve, and rotate secrets such as database credentials, API keys, and passwords. Secrets Manager supports a secret type for RDS databases, which allows you to select an existing RDS database instance and generate credentials for it. Secrets Manager encrypts the secret using AWS Key Management Service (AWS KMS) keys and enables automatic rotation of the secret at a specified interval. A Lambda function can use the AWS SDK or CLI to retrieve the secret from Secrets Manager and use it to connect to the database. Reference: Rotating your AWS Secrets Manager secrets

**NEW QUESTION 4**

A developer has observed an increase in bugs in the AWS Lambda functions that a development team has deployed in its Node.js application. To minimize these bugs, the developer wants to implement automated testing of Lambda functions in an environment that closely simulates the Lambda environment. The developer needs to give other developers the ability to run the tests locally. The developer also needs to integrate the tests into the team's continuous integration and continuous delivery (CI/CD) pipeline before the AWS Cloud Development Kit (AWS CDK) deployment. Which solution will meet these requirements?

- A. Create sample events based on the Lambda documentation
- B. Create automated test scripts that use the `cdk local invoke` command to invoke the Lambda function
- C. Check the response. Document the test scripts for the other developers on the team. Update the CI/CD pipeline to run the test scripts.
- D. Install a unit testing framework that reproduces the Lambda execution environment
- E. Create sample events based on the Lambda Documentation. Invoke the handler function by using a unit testing framework for the other developers on the team
- F. Check the response. Document how to run the unit testing framework.
- G. Update the CI/CD pipeline to run the unit testing framework.
- H. Install the AWS Serverless Application Model (AWS SAM) CLI tool. Use the `Sam local generate-event` command to generate sample events for automated test
- I. Create automated test scripts that use the `Sam local invoke` command to invoke the Lambda function
- J. Check the response. Document the test scripts for the other developers on the team. Update the CI/CD pipeline to run the test scripts.
- K. Create sample events based on the Lambda documentation
- L. Create a Docker container from the Node.js base image to invoke the Lambda function
- M. Check the response. Document how to run the Docker container for the other developers on the team. Update the CI/CD pipeline to run the Docker container.

**Answer: C**

**Explanation:**

This solution will meet the requirements by using AWS SAM CLI tool, which is a command line tool that lets developers locally build, test, debug, and deploy serverless applications defined by AWS SAM templates. The developer can use `sam local generate-event` command to generate sample events for different event sources such as API Gateway or S3. The developer can create automated test scripts that use `sam local invoke` command to invoke Lambda functions locally in an environment that closely simulates Lambda environment. The developer can check the response from Lambda functions and document how to run the test scripts for other developers on the team. The developer can also update CI/CD pipeline to run these test scripts before deploying with AWS CDK. Option A is not optimal because it will use `cdk local invoke` command, which does not exist in AWS CDK CLI tool. Option B is not optimal because it will use a unit testing framework that reproduces Lambda execution environment, which may not be accurate or consistent with Lambda environment. Option D is not optimal because it will create a Docker container from Node.js base image to invoke Lambda functions, which may introduce additional overhead and complexity for creating and running Docker containers.

References: [AWS Serverless Application Model (AWS SAM)], [AWS Cloud Development Kit (AWS CDK)]

**NEW QUESTION 5**

A company runs a payment application on Amazon EC2 instances behind an Application Load Balance. The EC2 instances run in an Auto Scaling group across multiple Availability Zones. The application needs to retrieve application secrets during the application startup and export the secrets as environment variables. These secrets must be encrypted at rest and need to be rotated every month. Which solution will meet these requirements with the LEAST development effort?

- A. Save the secrets in a text file and store the text file in Amazon S3. Provision a customer managed key. Use the key for secret encryption in Amazon S3. Read the contents of the text file and read the export as environment variables. Configure S3 Object Lambda to rotate the text file every month.
- B. Save the secrets as strings in AWS Systems Manager Parameter Store and use the default AWS Key Management Service (AWS KMS) key. Configure an Amazon EC2 user data script to retrieve the secrets during the startup and export as environment variables. Configure an AWS Lambda function to rotate the secrets in Parameter Store every month.
- C. Save the secrets as base64 encoded environment variables in the application properties.
- D. Retrieve the secrets during the application startup.
- E. Reference the secrets in the application code.
- F. Write a script to rotate the secrets saved as environment variables.
- G. Store the secrets in AWS Secrets Manager. Provision a new customer master key. Use the key to encrypt the secrets. Enable automatic rotation. Configure an Amazon EC2 user data script to programmatically retrieve the secrets during the startup and export as environment variables.

**Answer: D**

**Explanation:**

AWS Secrets Manager is a service that enables the secure management and rotation of secrets, such as database credentials, API keys, or passwords. By using

Secrets Manager, the company can avoid hardcoding secrets in the application code or properties files, and instead retrieve them programmatically during the application startup. Secrets Manager also supports automatic rotation of secrets by using AWS Lambda functions or built-in rotation templates. The company can provision a customer master key (CMK) to encrypt the secrets and use the AWS SDK or CLI to export the secrets as environment variables. References:

- ? What Is AWS Secrets Manager? - AWS Secrets Manager
- ? Rotating Your AWS Secrets Manager Secrets - AWS Secrets Manager
- ? Retrieving a Secret - AWS Secrets Manager

#### NEW QUESTION 6

An application that is hosted on an Amazon EC2 instance needs access to files that are stored in an Amazon S3 bucket. The application lists the objects that are stored in the S3 bucket and displays a table to the user. During testing, a developer discovers that the application does not show any objects in the list.

What is the MOST secure way to resolve this issue?

- A. Update the IAM instance profile that is attached to the EC2 instance to include the S3:\* permission for the S3 bucket.
- B. Update the IAM instance profile that is attached to the EC2 instance to include the S3:ListBucket permission for the S3 bucket.
- C. Update the developer's user permissions to include the S3:ListBucket permission for the S3 bucket.
- D. Update the S3 bucket policy by including the S3:ListBucket permission and by setting the Principal element to specify the account number of the EC2 instance.

**Answer: B**

#### Explanation:

IAM instance profiles are containers for IAM roles that can be associated with EC2 instances. An IAM role is a set of permissions that grant access to AWS resources. An IAM role can be used to allow an EC2 instance to access an S3 bucket by including the appropriate permissions in the role's policy. The S3:ListBucket permission allows listing the objects in an S3 bucket. By updating the IAM instance profile with this permission, the application on the EC2 instance can retrieve the objects from the S3 bucket and display them to the user. Reference: Using an IAM role to grant permissions to applications running on Amazon EC2 instances

#### NEW QUESTION 7

An online sales company is developing a serverless application that runs on AWS. The application uses an AWS Lambda function that calculates order success rates and stores the data in an Amazon DynamoDB table. A developer wants an efficient way to invoke the Lambda function every 15 minutes.

Which solution will meet this requirement with the LEAST development effort?

- A. Create an Amazon EventBridge rule that has a rate expression that will run the rule every 15 minute
- B. Add the Lambda function as the target of the EventBridge rule.
- C. Create an AWS Systems Manager document that has a script that will invoke the Lambda function on Amazon EC2. Use a Systems Manager Run Command task to run the shell script every 15 minutes.
- D. Create an AWS Step Functions state machine
- E. Configure the state machine to invoke the Lambda function execution role at a specified interval by using a Wait state
- F. Set the interval to 15 minutes.
- G. Provision a small Amazon EC2 instance
- H. Set up a cron job that invokes the Lambda function every 15 minutes.

**Answer: A**

#### Explanation:

The best solution for this requirement is option A. Creating an Amazon EventBridge rule that has a rate expression that will run the rule every 15 minutes and adding the Lambda function as the target of the EventBridge rule is the most efficient way to invoke the Lambda function periodically. This solution does not require any additional resources or development effort, and it leverages the built-in scheduling capabilities of EventBridge.

#### NEW QUESTION 8

A developer is creating a new REST API by using Amazon API Gateway and AWS Lambda. The development team tests the API and validates responses for the known use cases before deploying the API to the production environment.

The developer wants to make the REST API available for testing by using API Gateway locally. Which AWS Serverless Application Model Command Line Interface (AWS SAM CLI) subcommand will meet these requirements?

- A. Sam local invoke
- B. Sam local generate-event
- C. Sam local start-lambda
- D. Sam local start-api

**Answer: D**

#### Explanation:

? The sam local start-api subcommand allows you to run your serverless application locally for quick development and testing. It creates a local HTTP server that acts as a proxy for API Gateway and invokes your Lambda functions based on the AWS SAM template. You can use the sam local start-api subcommand to test your REST API locally by sending HTTP requests to the local endpoint.

#### NEW QUESTION 9

A company is using an AWS Lambda function to process records from an Amazon Kinesis data stream. The company recently observed slow processing of the records. A developer notices that the iterator age metric for the function is increasing and that the Lambda run duration is constantly above normal. Which actions should the developer take to increase the processing speed? (Choose two.)

- A. Increase the number of shards of the Kinesis data stream.
- B. Decrease the timeout of the Lambda function.
- C. Increase the memory that is allocated to the Lambda function.
- D. Decrease the number of shards of the Kinesis data stream.
- E. Increase the timeout of the Lambda function.

**Answer: AC**

**Explanation:**

Increasing the number of shards of the Kinesis data stream will increase the throughput and parallelism of the data processing. Increasing the memory that is allocated to the Lambda function will also increase the CPU and network performance of the function, which will reduce the run duration and improve the processing speed. Option B is not correct because decreasing the timeout of the Lambda function will not affect the processing speed, but may cause some records to fail if they exceed the timeout limit. Option D is not correct because decreasing the number of shards of the Kinesis data stream will decrease the throughput and parallelism of the data processing, which will slow down the processing speed. Option E is not correct because increasing the timeout of the Lambda function will not affect the processing speed, but may increase the cost of running the function.

References: [Amazon Kinesis Data Streams Scaling], [AWS Lambda Performance Tuning]

**NEW QUESTION 10**

A developer is working on a Python application that runs on Amazon EC2 instances. The developer wants to enable tracing of application requests to debug performance issues in the code.

Which combination of actions should the developer take to achieve this goal? (Select TWO)

- A. Install the Amazon CloudWatch agent on the EC2 instances.
- B. Install the AWS X-Ray daemon on the EC2 instances.
- C. Configure the application to write JSON-formatted logs to /var/log/cloudwatch.
- D. Configure the application to write trace data to /var/log/xray.
- E. Install and configure the AWS X-Ray SDK for Python in the application.

**Answer:** BE

**Explanation:**

This solution will meet the requirements by using AWS X-Ray to enable tracing of application requests to debug performance issues in the code. AWS X-Ray is a service that collects data about requests that the applications serve, and provides tools to view, filter, and gain insights into that data.

The developer can install the AWS X-Ray daemon on the EC2 instances, which is a software that listens for traffic on UDP port 2000, gathers raw segment data, and relays it to the X-Ray API. The developer can also install and configure the AWS X-Ray SDK for Python in the application, which is a library that enables instrumenting Python code to generate and send trace data to the X-Ray daemon. Option A is not optimal because it will install the Amazon CloudWatch agent on the EC2 instances, which is a software that collects metrics and logs from EC2 instances and on-premises servers, not application performance data. Option C is not optimal because it will configure the application to write JSON-formatted logs to /var/log/cloudwatch, which is not a valid path or destination for CloudWatch logs. Option D is not optimal because it will configure the application to write trace data to /var/log/xray, which is also not a valid path or destination for X-Ray trace data.

References: [AWS X-Ray], [Running the X-Ray Daemon on Amazon EC2]

**NEW QUESTION 10**

A company uses a custom root certificate authority certificate chain (Root CA Cert) that is 10 KB in size generate SSL certificates for its on-premises HTTPS endpoints. One of the company's cloud based applications has hundreds of AWS Lambda functions that pull data from these endpoints. A developer updated the trust store of the Lambda execution environment to use the Root CA Cert when the Lambda execution environment is initialized. The developer bundled the Root CA Cert as a text file in the Lambdas deployment bundle.

After 3 months of development the root CA Cert is no longer valid and must be updated. The developer needs a more efficient solution to update the Root CA Cert for all deployed Lambda functions. The solution must not include rebuilding or updating all Lambda functions that use the Root CA Cert. The solution must also work for all development, testing and production environment. Each environment is managed in a separate AWS account.

When combination of steps Would the developer take to meet these environments MOST cost-effectively? (Select TWO)

- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

This solution will meet the requirements by storing the Root CA Cert as a Secure String parameter in AWS Systems Manager Parameter Store, which is a secure and scalable service for storing and managing configuration data and secrets. The resource-based policy will allow IAM users in different AWS accounts and environments to access the parameter without requiring cross-account roles or permissions. The Lambda code will be refactored to load the Root CA Cert from the parameter store and modify the runtime trust store outside the Lambda function handler, which will improve performance and reduce latency by avoiding repeated calls to Parameter Store and trust store modifications for each invocation of the Lambda function. Option A is not optimal because it will use AWS Secrets Manager instead of AWS Systems Manager Parameter Store, which will incur additional costs and complexity for storing and managing a non-secret configuration data such as Root CA Cert. Option C is not optimal because it will deactivate the application secrets and monitor the application error logs temporarily, which will cause application downtime and potential data loss. Option D is not optimal because it will modify the runtime trust store inside the Lambda function handler, which will degrade performance and increase latency by repeating unnecessary operations for each invocation of the Lambda function.

References: AWS Systems Manager Parameter Store, [Using SSL/TLS to Encrypt a Connection to a DB Instance]

**NEW QUESTION 15**

A developer is using AWS Step Functions to automate a workflow The workflow defines each step as an AWS Lambda function task The developer notices that runs of the Step Functions state machine fail in the GetResource task with either an UlegalArgumentException error or a TooManyRequestsException error The developer wants the state machine to stop running when the state machine encounters an UlegalArgumentException error. The state machine needs to retry the GetResource task one additional time after 10 seconds if the state machine encounters a TooManyRequestsException error. If the second attempt fails, the developer wants the state machine to stop running.

How can the developer implement the Lambda retry functionality without adding unnecessary complexity to the state machine'?

- A. Add a Delay task after the GetResource tas
- B. Add a catcher to the GetResource tas
- C. Configure the catcher with an error type of TooManyRequestsExceptio
- D. Configure the next step to be the Delay task Configure the Delay task to wait for an interval of 10 seconds Configure the next step to be the GetResource task.
- E. Add a catcher to the GetResource task Configure the catcher with an error type of TooManyRequestsExceptio
- F. an interval of 10 seconds, and a maximum attempts value of 1. Configure the next step to be the GetResource task.
- G. Add a retrier to the GetResource task Configure the retrier with an error type of TooManyRequestsException, an interval of 10 seconds, and a maximum attempts value of 1.
- H. Duplicate the GetResource task Rename the new GetResource task to TryAgain Add a catcher to the original GetResource task Configure the catcher with an error type of TooManyRequestsExceptio
- I. Configure the next step to be TryAgain.

**Answer:** C

**Explanation:**

The best way to implement the Lambda retry functionality is to use the Retry field in the state definition of the GetResource task. The Retry field allows the developer to specify an array of retriers, each with an error type, an interval, and a maximum number of attempts. By setting the error type to TooManyRequestsException, the interval to 10 seconds, and the maximum attempts to 1, the developer can achieve the desired behavior of retrying the GetResource task once after 10 seconds if it encounters a TooManyRequestsException error. If the retry fails, the state machine will stop running. If the GetResource task encounters an UlegalArgumentException error, the state machine will also stop running without retrying, as this error type is not specified in the Retry field. References

- ? Error handling in Step Functions
- ? Handling Errors, Retries, and adding Alerting to Step Function State Machine Executions
- ? The Jitter Strategy for Step Functions Error Retries on the New Workflow Studio

**NEW QUESTION 19**

A company receives food orders from multiple partners. The company has a microservices application that uses Amazon API Gateway APIs with AWS Lambda integration. Each partner sends orders by calling a customized API that is exposed through API Gateway. The API call invokes a shared Lambda function to process the orders.

Partners need to be notified after the Lambda function processes the orders. Each partner must receive updates for only the partner's own orders. The company wants to add new partners in the future with the fewest code changes possible.

Which solution will meet these requirements in the MOST scalable way?

- A. Create a different Amazon Simple Notification Service (Amazon SNS) topic for each partner
- B. Configure the Lambda function to publish messages for each partner to the partner's SNS topic.
- C. Create a different Lambda function for each partner
- D. Configure the Lambda function to notify each partner's service endpoint directly.
- E. Create an Amazon Simple Notification Service (Amazon SNS) topic
- F. Configure the Lambda function to publish messages with specific attributes to the SNS topic
- G. Subscribe each partner to the SNS topic
- H. Apply the appropriate filter policy to the topic subscriptions.  
  - Create one Amazon Simple Notification Service (Amazon SNS) topic
- J. Subscribe all partners to the SNS topic.

**Answer:** C

**Explanation:**

Amazon Simple Notification Service (Amazon SNS) is a fully managed messaging service that enables pub/sub communication between distributed systems. The developer can create an SNS topic and configure the Lambda function to publish messages with specific attributes to the topic. The developer can subscribe each partner to the SNS topic and apply the appropriate filter policy to the topic subscriptions. This way, each partner will receive updates for only their own orders based on the message attributes. This solution will meet the requirements in the most scalable way and allow adding new partners in the future with minimal code changes.

References:

- ? [Amazon Simple Notification Service (SNS)]
- ? [Filtering Messages with Attributes - Amazon Simple Notification Service]

**NEW QUESTION 20**

A developer creates a static website for their department. The developer deploys the static assets for the website to an Amazon S3 bucket and serves the assets with Amazon CloudFront. The developer uses origin access control (OAC) on the CloudFront distribution to access the S3 bucket.

The developer notices users can access the root URL and specific pages but cannot access directories without specifying a file name. For example, /products/index.html works, but /products returns an error. The developer needs to enable accessing directories without specifying a file name without exposing the S3 bucket publicly.

Which solution will meet these requirements?

- A. Update the CloudFront distribution's settings to index.html as the default root object is set.  
  - Update the Amazon S3 bucket settings and enable static website hosting
- B. Specify index.html as the Index document. Update the S3 bucket policy to enable access.
- D. Update the CloudFront distribution's origin to use the S3 website endpoint.
- E. Create a CloudFront function that examines the request URL and appends index.html when directories are being accessed. Add the function as a viewer request CloudFront function to the CloudFront distribution's behavior.
- F. Create a custom error response on the CloudFront distribution with the HTTP error code set to the HTTP 404 Not Found response code and the response page path to /index.html. Set the HTTP response code to the HTTP 200 OK response code.

**Answer:** A

**Explanation:**

The simplest and most efficient way to enable accessing directories without specifying a file name is to update the CloudFront distribution's settings to index.html as the default root object. This will instruct CloudFront to return the index.html object when a user requests the root URL or a directory URL for the distribution. This solution does not require enabling static website hosting on the S3 bucket, creating a CloudFront function, or creating a custom error response. References

- ? Specifying a default root object
- ? cloudfront-default-root-object-configured
- ? How to setup CloudFront default root object?
- ? Ensure a default root object is configured for AWS Cloudfront ...

**NEW QUESTION 22**

A developer is creating an application that will give users the ability to store photos from their cellphones in the cloud. The application needs to support tens of thousands of users. The application uses an Amazon API Gateway REST API that is integrated with AWS Lambda functions to process the photos. The application stores details about the photos in Amazon DynamoDB.

Users need to create an account to access the application. In the application, users must be able to upload photos and retrieve previously uploaded photos. The photos will range in size from 300 KB to 5 MB.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use Amazon Cognito user pools to manage user account
- B. Create an Amazon Cognito user pool authorizer in API Gateway to control access to the AP
- C. Use the Lambda function to store the photos and details in the DynamoDB tabl
- D. Retrieve previously uploaded photos directly from the DynamoDB table.
- E. Use Amazon Cognito user pools to manage user account
- F. Create an Amazon Cognito user pool authorizer in API Gateway to control access to the AP
- G. Use the Lambda function to store the photos in Amazon S3. Store the object's S3 key as part of the photo details in the DynamoDB tabl
- H. Retrieve previously uploaded photos by querying DynamoDB for the S3 key.
- I. Create an IAM user for each user of the application during the sign-up proces
- J. Use IAM authentication to access the API Gateway AP

DynamoDB

- K. Use the Lambda function to store the photos in Amazon S3. Store the object's S3 key as part of the photo details in the
- L. Retrieve previously uploaded photos by querying DynamoDB for the S3 key.
- M. Create a users table in DynamoD
- N. Use the table to manage user account
- O. Create a Lambda authorizer that validates user credentials against the users tabl
- P. Integrate the Lambda authorizer with API Gateway to control access to the AP
- Q. Use the Lambda function to store the photos in Amazon S3. Store the object's S3 key as par of the photo details in the DynamoDB tabl
- R. Retrieve previously uploaded photos by querying DynamoDB for the S3 key.

**Answer: B**

**Explanation:**

Amazon Cognito user pools is a service that provides a secure user directory that scales to hundreds of millions of users. The developer can use Amazon Cognito user pools to manage user accounts and create an Amazon Cognito user pool authorizer in API Gateway to control access to the API. The developer can use the Lambda function to store the photos in Amazon S3, which is a highly scalable, durable, and secure object storage service. The developer can store the object's S3 key as part of the photo details in the DynamoDB table, which is a fast and flexible NoSQL database service. The developer can retrieve previously uploaded photos by querying DynamoDB for the S3 key and fetching the photos from S3. This solution will meet the requirements with the least operational overhead.

References:

- ? [Amazon Cognito User Pools]
- ? [Use Amazon Cognito User Pools - Amazon API Gateway]
- ? [Amazon Simple Storage Service (S3)]
- ? [Amazon DynamoDB]

**NEW QUESTION 23**

A company has an application that runs as a series of AWS Lambda functions. Each Lambda function receives data from an Amazon Simple Notification Service (Amazon SNS) topic and writes the data to an Amazon Aurora DB instance.

To comply with an information security policy, the company must ensure that the Lambda functions all use a single securely encrypted database connection string to access Aurora.

Which solution will meet these requirements'?

- A. Use IAM database authentication for Aurora to enable secure database connections for ail the Lambda functions.
- B. Store the credentials and read the credentials from an encrypted Amazon RDS DB instance.
- C. Store the credentials in AWS Systems Manager Parameter Store as a secure string parameter.
- D. Use Lambda environment variables with a shared AWS Key Management Service (AWS KMS) key for encryption.

**Answer: A**

**Explanation:**

This solution will meet the requirements by using IAM database authentication for Aurora, which enables using IAM roles or users to authenticate with Aurora databases instead of using passwords or other secrets. The developer can use IAM database authentication for Aurora to enable secure database connections for all the Lambda functions that access Aurora DB instance. The developer can create an IAM role with permission to connect to Aurora DB instance and attach it to each Lambda function. The developer can also configure Aurora DB instance to use IAM database authentication and enable encryption in transit using SSL certificates. This way, the Lambda functions can use a single securely encrypted database connection string to access Aurora without needing any secrets or passwords. Option B is not optimal because it will store the credentials and read them from an encrypted Amazon RDS DB instance, which may introduce additional costs and complexity for managing and accessing another RDS DB instance. Option C is not optimal because it will store the credentials in AWS Systems Manager Parameter Store as a secure string parameter, which may require additional steps or permissions to retrieve and decrypt the credentials from Parameter Store. Option D is not optimal because it will use Lambda environment variables with a shared AWS Key Management Service (AWS KMS) key for encryption, which may not be secure or scalable as environment variables are stored as plain text unless encrypted with AWS KMS. References: [IAM Database Authentication for MySQL and PostgreSQL], [Using SSL/TLS to Encrypt a Connection to a DB Instance]

**NEW QUESTION 25**

A developer must use multi-factor authentication (MFA) to access data in an Amazon S3 bucket that is in another AWS account. Which AWS Security Token Service (AWS STS) API operation should the developer use with the MFA information to meet this requirement?

- A. AssumeRoleWithWebidentity
- B. GetFederationToken
- C. AssumeRoleWithSAML
- D. AssumeRole

**Answer: D**

**Explanation:**

The AssumeRole API operation returns a set of temporary security credentials that can be used to access resources in another AWS account. The developer can specify the MFA device serial number and the MFA token code in the request parameters. This option enables the developer to use MFA to access data in an S3 bucket that is in another AWS account. The other options are not relevant or effective for this scenario. References

- ? AssumeRole
- ? Requesting Temporary Security Credentials

### NEW QUESTION 27

A company is building a web application on AWS. When a customer sends a request, the application will generate reports and then make the reports available to the customer within one hour. Reports should be accessible to the customer for 8 hours. Some reports are larger than 1 MB. Each report is unique to the customer. The application should delete all reports that are older than 2 days.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Generate the reports and then store the reports as Amazon DynamoDB items that have a specified TTL
- B. Generate a URL that retrieves the reports from DynamoDB
- C. Provide the URL to customers through the web application.
- D. Generate the reports and then store the reports in an Amazon S3 bucket that uses server-side encryption
- E. Attach the reports to an Amazon Simple Notification Service (Amazon SNS) message
- F. Subscribe the customer to email notifications from Amazon SNS.
- G. Generate the reports and then store the reports in an Amazon S3 bucket that uses server-side encryption
- H. Generate a presigned URL that contains an expiration date. Provide the URL to customers through the web application.
- I. Add S3 Lifecycle configuration rules to the S3 bucket to delete old reports.
- J. Generate the reports and then store the reports in an Amazon RDS database with a date stamp
- K. Generate a URL that retrieves the reports from the RDS database
- L. Provide the URL to customers through the web application
- M. Schedule an hourly AWS Lambda function to delete database records that have expired date stamps.

**Answer: C**

#### Explanation:

This solution will meet the requirements with the least operational overhead because it uses Amazon S3 as a scalable, secure, and durable storage service for the reports. The presigned URL will allow customers to access their reports for a limited time (8 hours) without requiring additional authentication. The S3 Lifecycle configuration rules will automatically delete the reports that are older than 2 days, reducing storage costs and complying with the data retention policy. Option A is not optimal because it will incur additional costs and complexity to store the reports as DynamoDB items, which have a size limit of 400 KB. Option B is not optimal because it will not provide customers with access to their reports within one hour, as Amazon SNS email delivery is not guaranteed. Option D is not optimal because it will require more operational overhead to manage an RDS database and a Lambda function for storing and deleting the reports.

References: Amazon S3 Presigned URLs, Amazon S3 Lifecycle

### NEW QUESTION 32

A financial company must store original customer records for 10 years for legal reasons. A complete record contains personally identifiable information (PII). According to local regulations, PII is available to only certain people in the company and must not be shared with third parties. The company needs to make the records available to third-party organizations for statistical analysis without sharing the PII.

A developer wants to store the original immutable record in Amazon S3. Depending on who accesses the S3 document, the document should be returned as is or with all the PII removed. The developer has written an AWS Lambda function to remove the PII from the document. The function is named `removePii`.

What should the developer do so that the company can meet the PII requirements while maintaining only one copy of the document?

- A. Set up an S3 event notification that invokes the `removePii` function when an S3 GET request is made
- B. Call Amazon S3 by using a GET request to access the object without PII.
- C. Set up an S3 event notification that invokes the `removePii` function when an S3 PUT request is made
- D. Call Amazon S3 by using a PUT request to access the object without PII.
- E. Create an S3 Object Lambda access point from the S3 console
- F. Select the `removePii` function
- G. Use S3 Access Points to access the object without PII.
- H. Create an S3 access point from the S3 console
- I. Use the access point name to call the `GetObjectLegalHold` S3 API function
- J. Pass in the `removePii` function name to access the object without PII.

**Answer: C**

#### Explanation:

S3 Object Lambda allows you to add your own code to process data retrieved from S3 before returning it to an application. You can use an AWS Lambda function to modify the data, such as removing PII, redacting confidential information, or resizing images. You can create an S3 Object Lambda access point and associate it with your Lambda function. Then, you can use the access point to request objects from S3 and get the modified data back. This way, you can maintain only one copy of the original

document in S3 and apply different transformations depending on who accesses it. Reference: Using AWS Lambda with Amazon S3

### NEW QUESTION 37

A company runs an application on AWS. The application stores data in an Amazon DynamoDB table. Some queries are taking a long time to run. These slow queries involve an attribute that is not the table's partition key or sort key.

The amount of data that the application stores in the DynamoDB table is expected to increase significantly. A developer must increase the performance of the queries.

Which solution will meet these requirements?

- A. Increase the page size for each request by setting the `Limit` parameter to be higher than the default value. Configure the application to retry any request that exceeds the provisioned throughput.
- B. Create a global secondary index (GSI). Set query attribute to be the partition key of the index.
- C. Perform a parallel scan operation by issuing individual scan requests in the parameters specify the segment for the scan requests and the total number of segments for the parallel scan.
- D. Turn on read capacity auto scaling for the DynamoDB table.
- E. Increase the maximum read capacity units (RCUs).

**Answer: B**

#### Explanation:

Creating a global secondary index (GSI) is the best solution to improve the performance of the queries that involve an attribute that is not the table's partition key or sort key. A GSI allows you to define an alternate key for your table and query the data using that key. This way, you can avoid scanning the entire table and

reduce the latency and cost of your queries. You should also follow the best practices for designing and using GSIs in DynamoDB12. References  
? Working with Global Secondary Indexes - Amazon DynamoDB  
? DynamoDB Performance & Latency - Everything You Need To Know

#### NEW QUESTION 42

An developer is building a serverless application by using the AWS Serverless Application Model (AWS SAM). The developer is currently testing the application in a development environment. When the application is nearly finished, the developer will need to set up additional testing and staging environments for a quality assurance team.

The developer wants to use a feature of the AWS SAM to set up deployments to multiple environments.

Which solution will meet these requirements with the LEAST development effort?

- A. Add a configuration file in TOML format to group configuration entries to every environment
- B. Add a table for each testing and staging environment
- C. Deploy updates to the environments by using the sam deploy command and the --config-env flag that corresponds to the each environment.
- D. Create additional AWS SAM templates for each testing and staging environment
- E. Write a custom shell script that uses the sam deploy command and the --template-file flag to deploy updates to the environments.
- F. Create one AWS SAM configuration file that has default parameter
- G. Perform updates to the testing and staging environments by using the --parameter-overrides flag in the AWS SAM CLI and the parameters that the updates will override.
- H. Use the existing AWS SAM template
- I. Add additional parameters to configure specific attributes for the serverless function and database table resources that are in each environment
- J. Deploy updates to the testing and staging environments by using the sam deploy command.

**Answer:** A

#### Explanation:

The correct answer is A. Add a configuration file in TOML format to group configuration entries to every environment. Add a table for each testing and staging environment. Deploy updates to the environments by using the sam deploy command and the --config-env flag that corresponds to the each environment.

\* A. Add a configuration file in TOML format to group configuration entries to every environment. Add a table for each testing and staging environment. Deploy updates to the environments by using the sam deploy command and the --config-env flag that corresponds to the each environment. This is correct. This solution will meet the requirements with the least development effort, because it uses a feature of the AWS SAM CLI that supports a project-level configuration file that can be used to configure AWS SAM CLI command parameter values1. The configuration file can have multiple environments, each with its own set of parameter values, such as stack name, region, capabilities, and more2. The developer can use the --config-env option to specify which environment to use when deploying the application3. This way, the developer can avoid creating multiple templates or scripts, or manually overriding parameters for each environment.

\* B. Create additional AWS SAM templates for each testing and staging environment. Write a custom shell script that uses the sam deploy command and the --template-file flag to

deploy updates to the environments. This is incorrect. This solution will not meet the requirements with the least development effort, because it requires creating and maintaining multiple templates and scripts for each environment. This can introduce duplication, inconsistency, and complexity in the deployment process.

\* C. Create one AWS SAM configuration file that has default parameters. Perform updates to the testing and staging environments by using the --parameter-overrides flag in the AWS SAM CLI and the parameters that the updates will override. This is incorrect. This solution will not meet the requirements with the least development effort, because it requires manually specifying and overriding parameters for each environment every time the developer deploys the application. This can be error-prone, tedious, and inefficient.

\* D. Use the existing AWS SAM template. Add additional parameters to configure specific attributes for the serverless function and database table resources that are in each environment. Deploy updates to the testing and staging environments by using the sam deploy command. This is incorrect. This solution will not meet the requirements with the least development effort, because it requires modifying the existing template and adding complexity to the resource definitions for each environment. This can also make it difficult to manage and track changes across different environments.

References:

? 1: AWS SAM CLI configuration file - AWS Serverless Application Model

? 2: Configuration file basics - AWS Serverless Application Model

? 3: Specify a configuration file - AWS Serverless Application Model

#### NEW QUESTION 46

A company wants to share information with a third party. The third party has an HTTP API endpoint that the company can use to share the information. The company has the required API key to access the HTTP API.

The company needs a way to manage the API key by using code. The integration of the API key with the application code cannot affect application performance.

Which solution will meet these requirements MOST securely?

- A. Mastered
- B. Not Mastered

**Answer:** A

#### Explanation:

AWS Secrets Manager is a service that helps securely store, rotate, and manage secrets such as API keys, passwords, and tokens. The developer can store the API credentials in AWS Secrets Manager and retrieve them at runtime by using the AWS SDK. This solution will meet the requirements of security, code management, and performance. Storing the API credentials in a local code variable or an S3 object is not secure, as it exposes the credentials to unauthorized access or leakage. Storing the API credentials in a DynamoDB table is also not secure, as it requires additional encryption and access control measures. Moreover, retrieving the credentials from S3 or DynamoDB may affect application performance due to network latency.

References:

? [What Is AWS Secrets Manager? - AWS Secrets Manager]

? [Retrieving a Secret - AWS Secrets Manager]

#### NEW QUESTION 47

A developer is testing an application that invokes an AWS Lambda function asynchronously. During the testing phase the Lambda function fails to process after two retries.

How can the developer troubleshoot the failure?

- A. Configure AWS CloudTrail logging to investigate the invocation failures.
- B. Configure Dead Letter Queues by sending events to Amazon SQS for investigation.

- C. Configure Amazon Simple Workflow Service to process any direct unprocessed events.
- D. Configure AWS Config to process any direct unprocessed events.

**Answer:** B

**Explanation:**

This solution allows the developer to troubleshoot the failure by capturing unprocessed events in a queue for further analysis. Dead Letter Queues (DLQs) are queues that store messages that could not be processed by a service, such as Lambda, for various reasons, such as configuration errors, throttling limits, or permissions issues. The developer can configure DLQs for Lambda functions by sending events to either an Amazon Simple Queue Service (SQS) queue or an Amazon Simple Notification Service (SNS) topic. The developer can then inspect the messages in the queue or topic to identify and fix the root cause of the failure. Configuring AWS CloudTrail logging will not capture invocation failures for asynchronous Lambda invocations, but only record API calls made by or on behalf of Lambda. Configuring Amazon Simple Workflow Service (SWF) or AWS Config will not process any direct unprocessed events, but require additional integration and configuration.

Reference: [Using AWS Lambda with DLQs], [Asynchronous invocation]

**NEW QUESTION 50**

A developer at a company needs to create a small application that makes the same API call once each day at a designated time. The company does not have infrastructure in the AWS Cloud yet, but the company wants to implement this functionality on AWS. Which solution meets these requirements in the MOST operationally efficient manner?

Use a Kubernetes cron job that runs on Amazon Elastic Kubernetes Service (Amazon EKS).

- A. Use an Amazon Linux crontab scheduled job that runs on Amazon EC2.
- C. Use an AWS Lambda function that is invoked by an Amazon EventBridge scheduled event.
- D. Use an AWS Batch job that is submitted to an AWS Batch job queue.

**Answer:** C

**Explanation:**

The correct answer is C. Use an AWS Lambda function that is invoked by an Amazon EventBridge scheduled event.

\* C. Use an AWS Lambda function that is invoked by an Amazon EventBridge scheduled event. This is correct. AWS Lambda is a serverless compute service that lets you run code without provisioning or managing servers. Lambda runs your code on a high-availability compute infrastructure and performs all of the administration of the compute resources, including server and operating system maintenance, capacity provisioning and automatic scaling, and logging<sup>1</sup>. Amazon EventBridge is a serverless event bus service that enables you to connect your applications with data from a variety of sources<sup>2</sup>. EventBridge can create rules that run on a schedule, either at regular intervals or at specific times and dates, and invoke targets such as Lambda functions<sup>3</sup>. This solution meets the requirements of creating a small application that makes the same API call once each day at a designated time, without requiring any infrastructure in the AWS Cloud or any operational overhead.

\* A. Use a Kubernetes cron job that runs on Amazon Elastic Kubernetes Service (Amazon EKS). This is incorrect. Amazon EKS is a fully managed Kubernetes service that allows you to run containerized applications on AWS<sup>4</sup>. Kubernetes cron jobs are tasks that run periodically on a given schedule<sup>5</sup>. This solution could meet the functional requirements of creating a small application that makes the same API call once each day at a designated time, but it would not be the most operationally efficient manner. The company would need to provision and manage an EKS cluster, which would incur additional costs and complexity.

\* B. Use an Amazon Linux crontab scheduled job that runs on Amazon EC2. This is incorrect. Amazon EC2 is a web service that provides secure, resizable compute capacity in the cloud<sup>6</sup>. Crontab is a Linux utility that allows you to schedule commands or scripts to run automatically at a specified time or date<sup>7</sup>. This solution could meet the functional requirements of creating a small application that makes the same API call once each day at a designated time, but it would not be the most operationally efficient manner. The company would need to provision and manage an EC2 instance, which would incur additional costs and complexity.

\* D. Use an AWS Batch job that is submitted to an AWS Batch job queue. This is incorrect. AWS Batch enables you to run batch computing workloads on the AWS or sequentially on

compute environments<sup>8</sup>. Batch jobs are units of work that can be submitted to job queues, where they are executed in parallel. This solution could meet the functional requirements of creating a small application that makes the same API call once each day at a designated time, but it would not be the most operationally efficient manner. The company would need to configure and manage an AWS Batch environment, which would incur additional costs and complexity.

References:

- ? 1: What is AWS Lambda? - AWS Lambda
- ? 2: What is Amazon EventBridge? - Amazon EventBridge
- ? 3: Creating an Amazon EventBridge rule that runs on a schedule - Amazon EventBridge
- ? 4: What is Amazon EKS? - Amazon EKS
- ? 5: CronJob - Kubernetes
- ? 6: What is Amazon EC2? - Amazon EC2
- ? 7: Crontab in Linux with 20 Useful Examples to Schedule Jobs - Tecmint
- ? 8: What is AWS Batch? - AWS Batch
- ? 9: Jobs - AWS Batch

**NEW QUESTION 52**

A company needs to distribute firmware updates to its customers around the world.

Which service will allow easy and secure control of the access to the downloads at the lowest cost?

- A. Use Amazon CloudFront with signed URLs for Amazon S3.
- B. Create a dedicated Amazon CloudFront Distribution for each customer.
- C. Use Amazon CloudFront with AWS Lambda@Edge.
- D. Use Amazon API Gateway and AWS Lambda to control access to an S3 bucket.

**Answer:** A

**Explanation:**

This solution allows easy and secure control of access to the downloads at the lowest cost because it uses a content delivery network (CDN) that can cache and distribute firmware updates to customers around the world, and uses a mechanism that can restrict access to specific files or versions. Amazon CloudFront is a CDN that can improve performance, availability, and security of web applications by delivering content from edge locations closer to customers. Amazon S3 is a storage service that can store firmware updates in buckets and objects. Signed URLs are URLs that include additional information, such as an expiration date and time, that give users temporary access to specific objects in S3 buckets. The developer can use CloudFront to serve firmware updates from S3 buckets and use signed URLs to control who can download them and for how long. Creating a dedicated CloudFront distribution for each customer will incur unnecessary costs and complexity. Using Amazon CloudFront with AWS Lambda@Edge will require additional programming overhead to implement custom logic at the edge locations. Using Amazon API Gateway and AWS Lambda to control access to an S3 bucket will also require additional programming overhead and may not provide optimal

performance or availability.

Reference: [Serving Private Content through CloudFront], [Using CloudFront with Amazon S3]

#### NEW QUESTION 54

A developer is migrating some features from a legacy monolithic application to use AWS Lambda functions instead. The application currently stores data in an Amazon Aurora DB cluster that runs in private subnets in a VPC. The AWS account has one VPC deployed. The Lambda functions and the DB cluster are deployed in the same AWS Region in the same AWS account.

The developer needs to ensure that the Lambda functions can securely access the DB cluster without crossing the public internet.

Which solution will meet these requirements?

- A. Configure the DB cluster's public access setting to Yes.
- B. Configure an Amazon RDS database proxy for the Lambda functions.
- C. Configure a NAT gateway and a security group for the Lambda functions.
- D. Configure the VPC, subnets, and a security group for the Lambda functions.

**Answer:** D

#### Explanation:

This solution will meet the requirements by allowing the Lambda functions to access the DB cluster securely within the same VPC without crossing the public internet. The developer can configure a VPC endpoint for RDS in a private subnet and assign it to the Lambda functions. The developer can also configure a security group for the Lambda functions that allows inbound traffic from the DB cluster on port 3306 (MySQL). Option A is not optimal because it will expose the DB cluster to public access, which may compromise its security and data integrity. Option B is not optimal because it will introduce additional latency and complexity to use an RDS database proxy for accessing the DB cluster from Lambda functions within the same VPC. Option C is not optimal because it will require additional costs and configuration to use a NAT gateway for accessing resources in private subnets from Lambda functions.

References: [Configuring a Lambda Function to Access Resources in a VPC]

#### NEW QUESTION 55

A developer at a company needs to create a small application that makes the same API call once each day at a designated time. The company does not have infrastructure in the AWS Cloud yet, but the company wants to implement this functionality on AWS.

Which solution meets these requirements in the MOST operationally efficient manner?

- A. Use a Kubernetes cron job that runs on Amazon Elastic Kubernetes Service (Amazon EKS)
- B. Use an Amazon Linux cron job that runs on Amazon EC2
- C. Use an AWS Lambda function that is invoked by an Amazon EventBridge scheduled event.
- D. Use an AWS Batch job that is submitted to an AWS Batch job queue.

**Answer:** C

#### Explanation:

This solution meets the requirements in the most operationally efficient manner because it does not require any infrastructure provisioning or management. The developer can create a Lambda function that makes the API call and configure an EventBridge rule that triggers the function once a day at a designated time. This is a serverless solution that scales automatically and only charges for the execution time of the function.

Reference: [Using AWS Lambda with Amazon EventBridge], [Schedule Expressions for Rules]

#### NEW QUESTION 59

A company is planning to securely manage one-time fixed license keys in AWS. The company's development team needs to access the license keys in automation scripts that run in Amazon EC2 instances and in AWS CloudFormation stacks.

Which solution will meet these requirements MOST cost-effectively?

- A. Amazon S3 with encrypted files prefixed with "config"
- B. AWS Secrets Manager secrets with a tag that is named SecretString
- C. AWS Systems Manager Parameter Store SecureString parameters
- D. CloudFormation NoEcho parameters

**Answer:** C

#### Explanation:

AWS Systems Manager Parameter Store is a service that provides secure, hierarchical storage for configuration data and secrets. Parameter Store supports SecureString parameters, which are encrypted using AWS Key Management Service (AWS KMS) keys. SecureString parameters can be used to store license keys in AWS and retrieve them securely from automation scripts that run in EC2 instances or CloudFormation stacks. Parameter Store is a cost-effective solution because it does not charge for storing parameters or API calls. Reference: Working with Systems Manager parameters

#### NEW QUESTION 62

A company is migrating its PostgreSQL database into the AWS Cloud. The company wants to use a database that will secure and regularly rotate database credentials. The company wants a solution that does not require additional programming overhead.

Which solution will meet these requirements?

- A. Mastered
- B. Not Mastered

**Answer:** A

#### Explanation:

This solution meets the requirements because it uses a PostgreSQL-compatible database that can secure and regularly rotate database credentials without requiring additional programming overhead. Amazon Aurora PostgreSQL is a relational database service that is compatible with PostgreSQL and offers high

performance, availability, and scalability. AWS Secrets Manager is a service that helps you protect secrets needed to access your applications, services, and IT resources. You can store database credentials in AWS Secrets Manager and use them to access your Aurora PostgreSQL database. You can also enable automatic rotation of your secrets according to a schedule or an event. AWS Secrets Manager handles the complexity of rotating secrets for you, such as generating new passwords and updating your database with the new credentials. Using Amazon DynamoDB for the database will not meet the requirements because it is a NoSQL database that is not compatible with PostgreSQL. Using AWS Systems Manager Parameter Store for storing and rotating database credentials will require additional programming overhead to integrate with your database.

Reference: [What Is Amazon Aurora?], [What Is AWS Secrets Manager?]

#### NEW QUESTION 65

A company built a new application in the AWS Cloud. The company automated the bootstrapping of new resources with an Auto Scaling group by using AWS CloudFormation templates. The bootstrap scripts contain sensitive data.

The company needs a solution that is integrated with CloudFormation to manage the sensitive data in the bootstrap scripts.

Which solution will meet these requirements in the MOST secure way?

- A. Put the sensitive data into a CloudFormation parameter
- B. Encrypt the CloudFormation templates by using an AWS Key Management Service (AWS KMS) key.
- C. Put the sensitive data into an Amazon S3 bucket Update the CloudFormation templates to download the object from Amazon S3 during bootstrap.
- D. Put the sensitive data into AWS Systems Manager Parameter Store as a secure string parameter
- E. Update the CloudFormation templates to use dynamic references to specify template values.
- F. Put the sensitive data into Amazon Elastic File System (Amazon EFS) Enforce EFS encryption after file system creation
- G. Update the CloudFormation templates to retrieve data from Amazon EFS.

Answer: C

#### Explanation:

This solution meets the requirements in the most secure way because it uses a service that is integrated with CloudFormation to manage sensitive data in encrypted form. AWS Systems Manager Parameter Store provides secure, hierarchical storage for configuration data management and secrets management. You can store sensitive data as secure string parameters, which are encrypted using an AWS Key Management Service (AWS KMS) key of your choice. You can also use dynamic references in your CloudFormation templates to specify template values that are stored in Parameter Store or Secrets Manager without having to include them in your templates. Dynamic references are resolved only during stack creation or update operations, which reduces exposure risks for sensitive data. Putting sensitive data into a CloudFormation parameter will not encrypt them or protect them from unauthorized access. Putting sensitive data into an Amazon S3 bucket or Amazon Elastic File System (Amazon EFS) will require additional configuration and integration with CloudFormation and may not provide fine-grained access control or encryption for sensitive data.

Reference: [What Is AWS Systems Manager Parameter Store?], [Using Dynamic References to Specify Template Values]

#### NEW QUESTION 68

A developer is creating an AWS Lambda function that searches for items from an Amazon DynamoDB table that contains customer contact information- The DynamoDB table items have the customer's email\_address as the partition key and additional properties such as customer\_type, name, and job\_title. The Lambda function runs whenever a user types a new character into the customer\_type text input The developer wants the search to return partial matches of all the email\_address property of a particular customer\_type The developer does not want to recreate the DynamoDB table.

What should the developer do to meet these requirements?

- A. Add a global secondary index (GSI) to the DynamoDB table with customer\_type as the partition key and email\_address as the sort key Perform a query operation on the GSI by using the begins\_with key condition expression With the email\_address property
- B. Add a global secondary index (GSI) to the DynamoDB table With email\_address as the partition key and customer\_type as the sort key Perform a query operation on the GSI by using the begins\_with key condition expression With the email\_address property.
- C. Add a local secondary index (LSI) to the DynamoDB table With customer\_type as the partition key and email\_address as the sort key Perform a query operation on the LSI by using the begins\_with key condition expression With the email\_address property
- D. Add a local secondary Index (LSI) to the DynamoDB table With job\_title as the partition key and email\_address as the sort key Perform a query operation on the LSI by using the begins\_with key condition expression With the email\_address property

Answer: A

#### Explanation:

By adding a global secondary index (GSI) to the DynamoDB table with customer\_type as the partition key and email\_address as the sort key, the developer can perform a query operation on the GSI using the Begins\_with key condition expression with the email\_address property. This will return partial matches of all email\_address properties of a specific customer\_type.

#### NEW QUESTION 71

A developer is writing an AWS Lambda function. The developer wants to log key events that occur while the Lambda function runs. The developer wants to include a unique identifier to associate the events with a specific function invocation. The developer adds the following code to the Lambda function:

```
function handler(event, context) {  
  
}
```

Which solution will meet this requirement?

- A. Obtain the request identifier from the AWS request ID field in the context object
- B. Configure the application to write logs to standard output.
- C. Obtain the request identifier from the AWS request ID field in the event object
- D. Configure the application to write logs to a file.
- E. Obtain the request identifier from the AWS request ID field in the event object
- F. Configure the application to write logs to standard output.
- G. Obtain the request identifier from the AWS request ID field in the context object

H. Configure the application to write logs to a file.

**Answer:** A

**Explanation:**

<https://docs.aws.amazon.com/lambda/latest/dg/nodejs-context.html> <https://docs.aws.amazon.com/lambda/latest/dg/nodejs-logging.html>

There is no explicit information for the runtime, the code is written in Node.js.

AWS Lambda is a service that lets developers run code without provisioning or managing servers. The developer can use the AWS request ID field in the context object to obtain a unique identifier for each function invocation. The developer can configure the application to write logs to standard output, which will be captured by Amazon CloudWatch Logs. This solution will meet the requirement of logging key events with a unique identifier.

References:

- ? [What Is AWS Lambda? - AWS Lambda]
- ? [AWS Lambda Function Handler in Node.js - AWS Lambda]
- ? [Using Amazon CloudWatch - AWS Lambda]

**NEW QUESTION 72**

A company is creating an application that processes csv files from Amazon S3 A developer has created an S3 bucket The developer has also created an AWS Lambda function to process the csv files from the S3 bucket

Which combination of steps will invoke the Lambda function when a csv file is uploaded to Amazon S3? (Select TWO.)

- A. Create an Amazon EventBridge rule Configure the rule with a pattern to match the S3 object created event
- B. Schedule an Amazon EventBridge rule to run a new Lambda function to scan the S3 bucket.
- C. Add a trigger to the existing Lambda functio
- D. Set the trigger type to EventBridge Select the Amazon EventBridge rule.
- E. Create a new Lambda function to scan the S3 bucket for recently added S3 objects
- F. Add S3 Lifecycle rules to invoke the existing Lambda function

**Answer:** AC

**Explanation:**

To invoke a Lambda function when a csv file is uploaded to Amazon S3, you can use Amazon EventBridge to create a rule that matches the S3 object created event. Then, you can add a trigger to the existing Lambda function and set the trigger type to EventBridge. This way, the Lambda function will be invoked whenever a new csv file is added to the S3 bucket. References

- ? Tutorial: Using an Amazon S3 trigger to invoke a Lambda function
- ? How to trigger my Lambda Function once the file is uploaded to s3 bucket
- ? Lambda Function to be invoked or triggered by S3(csv file upload ...

**NEW QUESTION 74**

A company is building a micro services app1 cation that consists of many AWS Lambda functions. The development team wants to use AWS Serverless Application Model (AWS SAM) templates to automatically test the Lambda functions. The development team plans to test a small percentage of traffic that is directed to new updates before the team commits to a full deployment of the application.

Which combination of steps will meet these requirements in the MOST operationally efficient way? (Select TWO.)

- A. Use AWS SAM CLI commands in AWS CodeDeploy lo invoke the Lambda functions lo lest the deployment
- B. Declare the EventInvokeConfig on the Lambda functions in the AWS SAM templates with OnSuccess and OnFailure configurations.  
Enable gradual deployments through AWS SAM templates.
- B:** Set the deployment preference type to Canary10Percen130Minutes Use hooks to test the deployment.
- E. Set the deployment preference type to Linear10PefcentEvery10Minutes Use hooks to test the deployment.

**Answer:** CD

**Explanation:**

This solution will meet the requirements by using AWS Serverless Application Model (AWS SAM) templates and gradual deployments to automatically test the Lambda functions. AWS SAM templates are configuration files that define serverless applications and resources such as Lambda functions. Gradual deployments are a feature of AWS SAM that enable deploying new versions of Lambda functions incrementally, shifting traffic gradually, and performing validation tests during deployment. The developer can enable gradual deployments through AWS SAM templates by adding a DeploymentPreference property to each Lambda function resource in the template. The developer can set the deployment preference type to Canary10Percent30Minutes, which means that 10 percent of traffic will be shifted to the new version of the Lambda function for 30 minutes before shifting 100 percent of traffic. The developer can also use hooks to test the deployment, which are custom Lambda functions that run before or after traffic shifting and perform validation tests or rollback actions.

References: [AWS Serverless Application Model (AWS SAM)], [Gradual Code Deployment]

**NEW QUESTION 77**

A developer is preparing to begin development of a new version of an application. The previous version of the application is deployed in a production environment. The developer needs to deploy fixes and updates to the current version during the development of the new version of the application. The code for the new version of the application is stored in AWS CodeCommit.

Which solution will meet these requirements?

- A. From the main branch, create a feature branch for production bug fixe
- B. Create a second feature branch from the main branch for development of the new version.
- C. Create a Git tag of the code that is currently deployed in productio
- D. Create a Git tag for the development of the new versio
- E. Push the two tags to the CodeCommit repository.
- F. From the main branch, create a branch of the code that is currently deployed in productio
- G. Apply an IAM policy that ensures no other other users can push or merge to the branch.
- H. Create a new CodeCommit repository for development of the new version of the applicatio
- I. Create a Git tag for the development of the new version.

**Answer:** A

**Explanation:**

? A feature branch is a branch that is created from the main branch to work on a specific feature or task<sup>1</sup>. Feature branches allow developers to isolate their work from the main branch and avoid conflicts with other changes<sup>1</sup>. Feature branches can be merged back to the main branch when the feature or task is completed and tested<sup>1</sup>.

? In this scenario, the developer needs to maintain two parallel streams of work: one for fixing and updating the current version of the application that is deployed in production, and another for developing the new version of the application. The developer can use feature branches to achieve this goal.

? The developer can create a feature branch from the main branch for production bug fixes. This branch will contain the code that is currently deployed in production, and any fixes or updates that need to be applied to it. The developer can push this branch to the CodeCommit repository and use it to deploy changes to the production environment.

? The developer can also create a second feature branch from the main branch for development of the new version of the application. This branch will contain the code that is under development for the new version, and any changes or enhancements that are part of it. The developer can push this branch to the CodeCommit repository and use it to test and deploy the new version of the application in a separate environment.

? By using feature branches, the developer can keep the main branch stable and clean, and avoid mixing code from different versions of the application. The developer can also easily switch between branches and merge them when needed.

#### NEW QUESTION 79

A developer is creating a service that uses an Amazon S3 bucket for image uploads. The service will use an AWS Lambda function to create a thumbnail of each image. Each time an image is uploaded, the service needs to send an email notification and create the thumbnail. The developer needs to configure the image processing and email notifications.

Which solution will meet these requirements?

- A. Create an Amazon Simple Notification Service (Amazon SNS) topic. Configure S3 event notifications with a destination of the SNS topic. Subscribe the Lambda function to the SNS topic. Create an email notification subscription to the SNS topic.
- B. Create an Amazon Simple Notification Service (Amazon SNS) topic. Configure S3 event notifications with a destination of the SNS topic. Subscribe the Lambda function to the SNS topic.
- C. Configure S3 event notifications with a destination of the SNS topic. Subscribe the Lambda function to the SNS topic.
- D. Subscribe the Lambda function to the SNS topic. Create an email notification subscription to the SNS topic.
- E. Create an Amazon Simple Queue Service (Amazon SQS) queue. Subscribe the SQS queue to the SNS topic. Create an email notification subscription to the SQS queue.
- F. Create an Amazon Simple Queue Service (Amazon SQS) queue. Configure S3 event notifications with a destination of the SQS queue. Subscribe the Lambda function to the SQS queue. Create an email notification subscription to the SQS queue.
- G. Create an Amazon Simple Queue Service (Amazon SQS) queue. Subscribe the SQS queue to the SNS topic. Create an email notification subscription to the SQS queue.
- H. Send S3 event notifications to Amazon EventBridge. Create an EventBridge rule that sends notifications to the SQS queue. Create an email notification subscription to the SQS queue.
- I. Create an EventBridge rule that runs the Lambda function when images are uploaded to the S3 bucket. Create an EventBridge rule that sends notifications to the SQS queue. Create an email notification subscription to the SQS queue.

**Answer:** A

#### Explanation:

This solution will allow the developer to receive notifications for each image uploaded to the S3 bucket, and also create a thumbnail using the Lambda function. The SNS topic will serve as a trigger for both the Lambda function and the email notification subscription. When an image is uploaded, S3 will send a notification to the SNS topic, which will trigger the Lambda function to create the thumbnail and also send an email notification to the specified email address.

#### NEW QUESTION 82

A company has an application that stores data in Amazon RDS instances. The application periodically experiences surges of high traffic that cause performance problems.

During periods of peak traffic, a developer notices a reduction in query speed in all database queries.

The team's technical lead determines that a multi-threaded and scalable caching solution should be used to offload the heavy read traffic. The solution needs to improve performance.

Which solution will meet these requirements with the LEAST complexity?

- A. Use Amazon ElastiCache for Memcached to offload read requests from the main database.
- B. Replicate the data to Amazon DynamoDB.
- C. Set up a DynamoDB Accelerator (DAX) cluster.
- D. Configure the Amazon RDS instances to use Multi-AZ deployment with one standby instance.
- E. Offload read requests from the main database to the standby instance.
- F. Use Amazon ElastiCache for Redis to offload read requests from the main database.

**Answer:** A

#### Explanation:

? Amazon ElastiCache for Memcached is a fully managed, multithreaded, and scalable in-memory key-value store that can be used to cache frequently accessed data and improve application performance<sup>1</sup>. By using Amazon ElastiCache for Memcached, the developer can reduce the load on the main database and handle high traffic surges more efficiently.

? To use Amazon ElastiCache for Memcached, the developer needs to create a cache cluster with one or more nodes, and configure the application to store and retrieve data from the cache cluster<sup>2</sup>. The developer can use any of the supported Memcached clients to interact with the cache cluster<sup>3</sup>. The developer can also use Auto Discovery to dynamically discover and connect to all cache nodes in a cluster<sup>4</sup>.

? Amazon ElastiCache for Memcached is compatible with the Memcached protocol, which means that the developer can use existing tools and libraries that work with Memcached<sup>1</sup>.

Amazon ElastiCache for Memcached also supports data partitioning, which allows the developer to distribute data among multiple nodes and scale out the cache cluster as needed.

? Using Amazon ElastiCache for Memcached is a simple and effective solution that meets the requirements with the least complexity. The developer does not need to change the database schema, migrate data to a different service, or use a different caching model. The developer can leverage the existing Memcached ecosystem and easily integrate it with the application.

#### NEW QUESTION 87

A developer is trying to get data from an Amazon DynamoDB table called demoman-table. The developer configured the AWS CLI to use a specific IAM user's credentials and ran the following command.

```
aws dynamodb get-item --table-name demoman-table --key '{"id": {"N": "1993"}}'
```

The command returned errors and no rows were returned. What is the MOST likely cause of these issues?

- A. The command is incorrect; it should be rewritten to use put-item with a string argument
- B. The developer needs to log a ticket with AWS Support to enable access to the demoman-table
- C. Amazon DynamoDB cannot be accessed from the AWS CLI and needs to be called via the REST API
- D. The IAM user needs an associated policy with read access to demoman-table

**Answer:** D

**Explanation:**

This solution will most likely solve the issues because it will grant the IAM user the necessary permission to access the DynamoDB table using the AWS CLI command. The error message indicates that the IAM user does not have sufficient access rights to perform the scan operation on the table. Option A is not optimal because it will change the command to use put-item instead of scan, which will not achieve the desired result of getting data from the table. Option B is not optimal because it will involve contacting AWS Support, which may not be necessary or efficient for this issue. Option C is not optimal because it will state that DynamoDB cannot be accessed from the AWS CLI, which is incorrect as DynamoDB supports AWS CLI commands.

References: [AWS CLI for DynamoDB](#), [IAM Policies for DynamoDB](#)

**NEW QUESTION 91**

A company built an online event platform. For each event, the company organizes quizzes and generates leaderboards that are based on the quiz scores. The company stores the leaderboard data in Amazon DynamoDB and retains the data for 30 days after an event is complete. The company then uses a scheduled job to delete the old leaderboard data.

The DynamoDB table is configured with a fixed write capacity. During the months when many events occur, the DynamoDB write API requests are throttled when the scheduled delete job runs.

A developer must create a long-term solution that deletes the old leaderboard data and optimizes write throughput.

Which solution meets these requirements?

- A. Configure a TTL attribute for the leaderboard data.
- B. Use DynamoDB Streams to schedule and delete the leaderboard data.
- C. Use AWS Step Functions to schedule and delete the leaderboard data.
- D. Set a higher write capacity when the scheduled delete job runs.

**Answer:** A

**Explanation:**

"Deletes the item from your table without consuming any write throughput." <https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/TTL.html>

**NEW QUESTION 96**

A company has an analytics application that uses an AWS Lambda function to process transaction data asynchronously. A developer notices that asynchronous invocations of the Lambda function sometimes fail. When failed Lambda function invocations occur, the developer wants to invoke a second Lambda function to handle errors and log details.

Which solution will meet these requirements?

- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

Configuring a Lambda function destination with a failure condition is the best solution for invoking a second Lambda function to handle errors and log details. A Lambda function destination is a resource that Lambda sends events to after a function is invoked. The developer can specify the destination type as Lambda function and the ARN of the error-handling Lambda function as the resource. The developer can also specify the failure condition, which means that the destination is invoked only when the initial Lambda function fails. The destination event will include the response from the initial function, the request ID, and the timestamp. The other solutions are either not feasible or not efficient. Enabling AWS X-Ray active tracing on the initial Lambda function will help to monitor and troubleshoot the function performance, but it will not automatically invoke the error-handling Lambda function. Configuring a Lambda function trigger with a failure condition is not a valid option, as triggers are used to invoke Lambda functions, not to send events from Lambda functions. Creating a status check alarm on the initial Lambda function will incur additional costs and complexity, and it will not capture the details of the failed invocations. References:

- ? [Using AWS Lambda destinations](#)
- ? [Asynchronous invocation - AWS Lambda](#)
- ? [AWS Lambda Destinations: What They Are and Why to Use Them](#)
- ? [AWS Lambda Destinations: A Complete Guide | Dashbird](#)

**NEW QUESTION 101**

A developer created an AWS Lambda function that performs a series of operations that involve multiple AWS services. The function's duration time is higher than normal. To determine the cause of the issue, the developer must investigate traffic between the services without changing the function code.

Which solution will meet these requirements?

- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

AWS X-Ray is a service that helps you analyze and debug your applications. You can use X-Ray to trace requests made to your Lambda function and other AWS services, and identify performance bottlenecks and errors. Enabling active tracing in your Lambda function allows X-Ray to collect data from the function invocation and the downstream services that it calls. You can then review the logs and service maps in X-Ray to diagnose the issue. References:

- ? [Monitoring and troubleshooting Lambda functions - AWS Lambda](#)
- ? [Using AWS Lambda with AWS X-Ray](#)
- ? [Troubleshoot Lambda function cold start issues | AWS re:Post](#)

**NEW QUESTION 104**

A company needs to set up secure database credentials for all its AWS Cloud resources. The company's resources include Amazon RDS DB instances Amazon DocumentDB clusters and Amazon Aurora DB instances. The company's security policy mandates that database credentials be encrypted at rest and rotated at a regular interval.

Which solution will meet these requirements MOST securely?

- A. Set up IAM database authentication for token-based access
- B. Generate user tokens to provide centralized access to RDS DB instance
- C. Amazon DocumentDB clusters and Aurora DB instances.
- D. Create parameters for the database credentials in AWS Systems Manager Parameter Store Set the Type parameter to Secure String and set up automatic rotation on the parameters.
- E. Set up automatic rotation on the parameters.
- F. Store the database access credentials as an encrypted Amazon S3 object in an S3 bucket Block all public access on the S3 bucket and set up automatic rotation on the encryption key.
- G. Use S3 server-side encryption to set up automatic rotation on the encryption key.
- H. Create an AWS Lambda function by using the SecretsManagerRotationTemplate template in the AWS Secrets Manager console
- I. Create secrets for the database credentials in Secrets Manager Set up secrets rotation on a schedule.

**Answer:** D

**Explanation:**

This solution will meet the requirements by using AWS Secrets Manager, which is a service that helps protect secrets such as database credentials by encrypting them with AWS Key Management Service (AWS KMS) and enabling automatic rotation of secrets. The developer can create an AWS Lambda function by using the SecretsManagerRotationTemplate template in the AWS Secrets Manager console, which provides a sample code for rotating secrets for RDS DB instances, Amazon DocumentDB clusters, and Amazon Aurora DB instances. The developer can also create secrets for the database credentials in Secrets Manager, which encrypts them at rest and provides secure access to them. The developer can set up secrets rotation on a schedule, which changes the database credentials periodically according to a specified interval or event. Option A is not optimal because it will set up IAM database authentication for token-based access, which may not be compatible with all database engines and may require additional configuration and management of IAM roles or users. Option B is not optimal because it will create parameters for the database credentials in AWS Systems Manager Parameter Store, which does not support automatic rotation of secrets. Option C is not optimal because it will store the database access credentials as an encrypted Amazon S3 object in an S3 bucket, which may introduce additional costs and complexity for accessing and securing the data.

References: [AWS Secrets Manager], [Rotating Your AWS Secrets Manager Secrets]

**NEW QUESTION 105**

A developer is using AWS Amplify Hosting to build and deploy an application. The developer is receiving an increased number of bug reports from users. The developer wants to add end-to-end testing to the application to eliminate as many bugs as possible before the bugs reach production.

Which solution should the developer implement to meet these requirements?

- A. Run the amplify add test command in the Amplify CLI.
- B. Create unit tests in the application.
- C. Deploy the unit tests by using the amplify push command in the Amplify CLI.
- D. Add a test phase to the amplify.yml build settings for the application.
- E. Add a test phase to the aws-exports.js file for the application.

**Answer:** C

**Explanation:**

The solution that will meet the requirements is to add a test phase to the amplify.yml build settings for the application. This way, the developer can run end-to-end tests on every code commit and catch any bugs before deploying to production. The other options either do not support end-to-end testing, or do not run tests automatically.

Reference: End-to-end testing

**NEW QUESTION 109**

A company has an ecommerce application. To track product reviews, the company's development team uses an Amazon DynamoDB table.

Every record includes the following

- A Review ID a 16-digit universally unique identifier (UUID)
- A Product ID and User ID 16 digit UUIDs that reference other tables
- A Product Rating on a scale of 1-5
- An optional comment from the user

The table partition key is the Review ID. The most performed query against the table is to find the 10 reviews with the highest rating for a given product.

Which index will provide the FASTEST response for this query?

- A. A global secondary index (GSI) with Product ID as the partition key and Product Rating as the sort key
- B. A global secondary index (GSI) with Product ID as the partition key and Review ID as the sort key
- C. A local secondary index (LSI) with Product ID as the partition key and Product Rating as the sort key
- D. A local secondary index (LSI) with Review ID as the partition key and Product ID as the sort key

**Answer:** A

**Explanation:**

This solution allows the fastest response for the query because it enables the query to use a single partition key value (the Product ID) and a range of sort key values (the Product Rating) to find the matching items. A global secondary index (GSI) is an index that has a partition key and an optional sort key that are different from those on the base table. A GSI can be created at any time and can be queried or scanned independently of the base table. A local secondary index (LSI) is an index that has the same partition key as the base table, but a different sort key. An LSI can only be created when the base table is created and must be queried together with the base table partition key. Using a GSI with Product ID as the partition key and Review ID as the sort key will not allow the query to use a range of sort key values to find the highest ratings. Using an LSI with Product ID as the partition key and Product Rating as the sort key will not work because Product ID is not the partition key of the base table. Using an LSI with Review ID as the partition key and Product ID as the sort key will not allow the query to use a single partition key value to find the matching items.

Reference: [Global Secondary Indexes], [Querying]

**NEW QUESTION 111**

A developer is working on a web application that uses Amazon DynamoDB as its data store. The application has two DynamoDB tables: one table named `artists` and one table named `songs`. The `artists` table has `artistName` as the partition key. The `songs` table has `songName` as the partition key and `artistName` as the sort key.

The table usage patterns include the retrieval of multiple songs and artists in a single database operation from the webpage. The developer needs a way to retrieve this information with minimal network traffic and optimal application performance.

Which solution will meet these requirements?

- A. Perform a `BatchGetItem` operation that returns items from the two tables.
- B. Use the list of `songName` `artistName` keys for the `songs` table and the list of `artistName` key for the `artists` table.
- C. Create a local secondary index (LSI) on the `songs` table that uses `artistName` as the partition key. Perform a query operation for each `artistName` on the `songs` table that filters by the list of `songName`. Perform a query operation for each `artistName` on the `artists` table.
- D. Perform a `BatchGetItem` operation on the `songs` table that uses the `songName/artistName` key.
- E. Perform a `BatchGetItem` operation on the `artists` table that uses `artistName` as the key.
- F. Perform a `Scan` operation on each table that filters by the list of `songName/artistName` for the `songs` table and the list of `artistName` in the `artists` table.

**Answer:** A

**Explanation:**

`BatchGetItem` can return one or multiple items from one or more tables. For reference check the link below  
[https://docs.aws.amazon.com/amazondynamodb/latest/APIReference/API\\_BatchGetItem.html](https://docs.aws.amazon.com/amazondynamodb/latest/APIReference/API_BatchGetItem.html)

**NEW QUESTION 114**

A company is migrating legacy internal applications to AWS. Leadership wants to rewrite the internal employee directory to use native AWS services. A developer needs to create a solution for storing employee contact details and high-resolution photos for use with the new application.

Which solution will enable the search and retrieval of each employee's individual details and high-resolution photos using AWS APIs?

- A. Encode each employee's contact information and photos using Base64. Store the information in an Amazon DynamoDB table using a sort key.
- B. Store each employee's contact information in an Amazon DynamoDB table along with the object keys for the photos stored in Amazon S3.
- C. Use Amazon Cognito user pools to implement the employee directory in a fully managed software-as-a-service (SaaS) method.
- D. Store employee contact information in an Amazon RDS DB instance with the photos stored in Amazon Elastic File System (Amazon EFS).

**Answer:** B

**Explanation:**

Amazon DynamoDB is a fully managed NoSQL database service that provides fast and consistent performance with seamless scalability. The developer can store each employee's contact information in a DynamoDB table along with the object keys for the photos stored in Amazon S3. Amazon S3 is an object storage service that offers industry-leading scalability, data availability, security, and performance. The developer can use AWS APIs to search and retrieve the employee details and photos from DynamoDB and S3.

References:

? [Amazon DynamoDB]

? [Amazon Simple Storage Service (S3)]

**NEW QUESTION 115**

A developer uses AWS CloudFormation to deploy an Amazon API Gateway API and an AWS Step Functions state machine. The state machine must reference the API Gateway API after the CloudFormation template is deployed. The developer needs a solution that uses the state machine to reference the API Gateway endpoint.

Which solution will meet these requirements MOST cost-effectively?

- A. Configure the CloudFormation template to reference the API endpoint in the `DefinitionSubstitutions` property for the AWS StepFunctions `StateMachine` resource.
- B. Configure the CloudFormation template to store the API endpoint in an environment variable for the `AWS::StepFunctions::StateMachine` resource. Configure the state machine to reference the environment variable.
- C. Configure the CloudFormation template to store the API endpoint in a standard AWS: `SecretsManager` `Secret` resource. Configure the state machine to reference the resource.
- D. Configure the CloudFormation template to store the API endpoint in a standard `AWS::AppConfig::ConfigurationProfile` resource. Configure the state machine to reference the resource.

**Answer:** A

**Explanation:**

The most cost-effective solution is to use the `DefinitionSubstitutions` property of the `AWS::StepFunctions::StateMachine` resource to inject the API endpoint as a variable in the state machine definition. This way, the developer can use the intrinsic function

`Fn::GetAtt` to get the API endpoint from the `AWS::ApiGateway::RestApi` resource, and pass it to the state machine without creating any additional resources or environment variables. The other solutions involve creating and managing extra resources, such as Secrets Manager secrets or AppConfig configuration profiles, which incur additional costs and complexity. References

? `AWS::StepFunctions::StateMachine` - AWS CloudFormation

? Call API Gateway with Step Functions - AWS Step Functions

? `amazon-web-services` `aws-api-gateway` `terraform` `aws-step-functions`

**NEW QUESTION 120**

A company has deployed infrastructure on AWS. A development team wants to create an AWS Lambda function that will retrieve data from an Amazon Aurora database. The Amazon Aurora database is in a private subnet in company's VPC. The VPC is named `VPC1`. The data is relational in nature. The Lambda function needs to access the data

securely.

Which solution will meet these requirements?

- A. Create the Lambda function

- B. Configure VPC1 access for the functio
- C. Attach a security group named SG1 to both the Lambda function and the databas
- D. Configure the security group inbound and outbound rules to allow TCP traffic on Port 3306.
- E. Create and launch a Lambda function in a new public subnet that is in a new VPC named VPC2. Create a peering connection between VPC1 and VPC2.
- F. Create the Lambda functio
- G. Configure VPC1 access for the functio
- H. Assign a security group named SG1 to the Lambda functio
- I. Assign a second security group named SG2 to the databas
- J. Add an inbound rule to SG1 to allow TCP traffic from Port 3306.
- K. Export the data from the Aurora database to Amazon S3. Create and launch a Lambda function in VPC1. Configure the Lambda function query the data from Amazon S3.

**Answer:** A

**Explanation:**

AWS Lambda is a service that lets you run code without provisioning or managing servers. Lambda functions can be configured to access resources in a VPC, such as an Aurora database, by specifying one or more subnets and security groups in the VPC settings of the function. A security group acts as a virtual firewall that controls inbound and outbound traffic for the resources in a VPC. To allow a Lambda function to communicate with an Aurora database, both resources need to be associated with the same security group, and the security group rules need to allow TCP traffic on Port 3306, which is the default port for MySQL databases. Reference: [Configuring a Lambda function to access resources in a VPC]

**NEW QUESTION 121**

A team of developed is using an AWS CodePipeline pipeline as a continuous integration and continuous delivery (CI/CD) mechanism for a web application. A developer has written unit tests to programmatically test the functionality of the application code. The unit tests produce a test report that shows the results of each individual check. The developer now  
 wants to run these tests automatically during the CI/CD process.

- A. Write a Git pre-commit hook that runs the test before every commi
- B. Ensure that each developer who is working on the project has the pre-commit hook instated locall
- C. Review the test report and resolve any issues before pushing changes to AWS CodeCommit.
- D. Add a new stage to the pipelin
- E. Use AWS CodeBuild as the provide
- F. Add the new stage after the stage that deploys code revisions to the test environmen
- G. Write a buildspec that fails the CodeBuild stage if any test does not pas
- H. Use the test reports feature of Codebuild to integrate the report with the CodoBuild consol
- I. View the test results in CodeBuild Resolve any issues.
- J. Add a new stage to the pipelin
- K. Use AWS CodeBuild at the provide
- L. Add the new stage before the stage that deploys code revisions to the test environmen
- M. Write a buildspec that fails the CodeBuild stage it any test does not pas
- N. Use the test reports feature of CodeBuild to integrate the report with the CodeBuild consol
- O. View the test results in codeBuild Resolve any issues.
- P. Add a new stage to the pipelin
- Q. Use Jenkins as the provide
- R. Configure CodePipeline to use Jenkins to run the unit test
- S. Write a Jenkinsfile that fails the stage if any test does not pas
- T. Use the test report plugin for Jenkins to integrate the repot with the Jenkins dashboar
- . View the test results in Jenkin
- . Resolve any issues.

**Answer:** C

**Explanation:**

The solution that will meet the requirements is to add a new stage to the pipeline. Use AWS CodeBuild as the provider. Add the new stage before the stage that deploys code revisions to the test environment. Write a buildspec that fails the CodeBuild stage if any test does not pass. Use the test reports feature of CodeBuild to integrate the report with the CodeBuild console. View the test results in CodeBuild. Resolve any issues. This way, the developer can run the unit tests automatically during the CI/CD process and catch any bugs before deploying to the test environment. The developer can also use the test reports feature of CodeBuild to view and analyze the test results in a graphical interface. The other options either involve running the tests manually, running them after deployment, or using a different provider that requires additional configuration and integration. Reference: Test reports for CodeBuild

**NEW QUESTION 124**

A company's website runs on an Amazon EC2 instance and uses Auto Scaling to scale the environment during peak times. Website users across the world ate experiencing high latency flue lo sialic content on theEC2 instance. even during non-peak hours. When companion of steps mill resolves the latency issue? (Select TWO)

- A. Double the Auto Scaling group's maximum number of servers
- B. Host the application code on AWS lambda
- C. Scale vertically by resizing the EC2 instances
- D. Create an Amazon Cloudfront distribution to cache the static content
- E. Store the application's sialic content in Amazon S3

**Answer:** DE

**Explanation:**

The combination of steps that will resolve the latency issue is to create an Amazon CloudFront distribution to cache the static content and store the application's static content in Amazon S3. This way, the company can use CloudFront to deliver the static content from edge locations that are closer to the website users, reducing latency and improving performance. The company can also use S3 to store the static content reliably and cost-effectively, and integrate it with CloudFront easily. The other options either do not address the latency issue, or are not necessary or feasible for the given scenario. Reference: Using Amazon S3 Origins and Custom Origins for Web Distributions

### NEW QUESTION 127

A company is expanding the compatibility of its photo-snaring mobile app to hundreds of additional devices with unique screen dimensions and resolutions. Photos are stored in Amazon S3 in their original format and resolution. The company uses an Amazon CloudFront distribution to serve the photos. The app includes the dimension and resolution of the display as GET parameters with every request.

A developer needs to implement a solution that optimizes the photos that are served to each device to reduce load time and increase photo quality. Which solution will meet these requirements MOST cost-effectively?

- A. Use S3 Batch Operations to invoke an AWS Lambda function to create new variants of the photos with the required dimensions and resolution
- B. Create a dynamic CloudFront origin that automatically maps the request of each device to the corresponding photo variant.
- C. Use S3 Batch Operations to invoke an AWS Lambda function to create new variants of the photos with the required dimensions and resolution
- D. Create a Lambda@Edge function to route requests to the corresponding photo variant by using request headers.
- E. Create a Lambda@Edge function that optimizes the photos upon request and returns the photos as a response
- F. Change the CloudFront TTL cache policy to the maximum value possible.

Create a Lambda@Edge function that optimizes the photos upon request and returns the photos as a response

G. In the same function store a copy of the processed photos on Amazon S3 for subsequent requests.

**Answer: D**

#### Explanation:

This solution meets the requirements most cost-effectively because it optimizes the photos on demand and caches them for future requests. Lambda@Edge allows the developer to run Lambda functions at AWS locations closer to viewers, which can reduce latency and improve photo quality. The developer can create a Lambda@Edge function that uses the GET parameters from each request to optimize the photos with the required dimensions and resolutions and returns them as a response. The function can also store a copy of the processed photos on Amazon S3 for subsequent requests, which can reduce processing time and costs. Using S3 Batch Operations to create new variants of the photos will incur additional storage costs and may not cover all possible dimensions and resolutions. Creating a dynamic CloudFront origin or a Lambda@Edge function to route requests to corresponding photo variants will require maintaining a mapping of device types and photo variants, which can be complex and error-prone.

Reference: [Lambda@Edge Overview], [Resizing Images with Amazon CloudFront & Lambda@Edge]

### NEW QUESTION 128

A developer is creating an AWS Lambda function in VPC mode. An Amazon S3 event will invoke the Lambda function when an object is uploaded into an S3 bucket. The Lambda function will process the object and produce some analytic results that will be recorded into a file. Each processed object will also generate a log entry that will be recorded into a file.

Other Lambda functions, AWS services, and on-premises resources must have access to the result files and log file. Each log entry must also be appended to the same shared log file. The developer needs a solution that can share files and append results into an existing file.

Which solution should the developer use to meet these requirements?

- A. Create an Amazon Elastic File System (Amazon EFS) file system
- B. Mount the EFS file system in Lambda
- C. Store the result files and log file in the mount point
- D. Append the log entries to the log file.
- E. Create an Amazon Elastic Block Store (Amazon EBS) Multi-Attach enabled volume. Attach the EBS volume to all Lambda function. download the log file, append the log entries, and upload the modified log file to Amazon EBS
- F. Update the Lambda function code to
- G. Create a reference to the /tmp/local directory
- H. Store the result files and log file by using the directory reference
- I. Append the log entry to the log file.
- J. Create a reference to the /opt storage directory. Store the result files and log file by using the directory reference. Append the log entry to the log file

**Answer: A**

#### Explanation:

<https://aws.amazon.com/blogs/compute/using-amazon-efs-for-aws-lambda-in-your-serverless-applications/>

### NEW QUESTION 131

A developer is building a web application that uses Amazon API Gateway to expose an AWS Lambda function to process requests from clients. During testing, the developer notices that the API Gateway times out even though the Lambda function finishes under the set time limit.

Which of the following API Gateway metrics in Amazon CloudWatch can help the developer troubleshoot the issue? (Choose two.)

- A. CacheHitCount
- B. IntegrationLatency
- C. CacheMissCount
- D. Latency
- E. Count

**Answer: BD**

#### Explanation:

Amazon API Gateway is a service that enables developers to create, publish, maintain, monitor, and secure APIs at any scale. Amazon CloudWatch is a service that monitors AWS resources and applications. API Gateway provides several CloudWatch metrics to help developers troubleshoot issues with their APIs. Two of the metrics that can help the developer troubleshoot the issue of API Gateway timing out are:

? IntegrationLatency: This metric measures the time between when API Gateway relays a request to the backend and when it receives a response from the backend. A high value for this metric indicates that the backend is taking too long to respond and may cause API Gateway to time out.

? Latency: This metric measures the time between when API Gateway receives a request from a client and when it returns a response to the client. A high value for this metric indicates that either the integration latency is high or API Gateway is taking too long to process the request or response.

References:

? [What Is Amazon API Gateway? - Amazon API Gateway]

? [Amazon API Gateway Metrics and Dimensions - Amazon CloudWatch]

? [Troubleshooting API Errors - Amazon API Gateway]

#### NEW QUESTION 136

A developer is designing a serverless application with two AWS Lambda functions to process photos. One Lambda function stores objects in an Amazon S3 bucket and stores the associated metadata in an Amazon DynamoDB table. The other Lambda function fetches the objects from the S3 bucket by using the metadata from the DynamoDB table. Both Lambda functions use the same Python library to perform complex computations and are approaching the quota for the maximum size of zipped deployment packages.

What should the developer do to reduce the size of the Lambda deployment packages with the LEAST operational overhead?

- A. Package each Python library in its own .zip file archive
- B. Deploy each Lambda function with its own copy of the library.
- C. Create a Lambda layer with the required Python library
- D. Use the Lambda layer in both Lambda functions.
- E. Combine the two Lambda functions into one Lambda function
- F. Deploy the Lambda function as a single .zip file archive.
- G. Download the Python library to an S3 bucket
- H. Program the Lambda functions to reference the object URLs.

**Answer:** B

#### Explanation:

AWS Lambda is a service that lets developers run code without provisioning or managing servers. Lambda layers are a distribution mechanism for libraries, custom runtimes, and other dependencies. The developer can create a Lambda layer with the

required Python library and use the layer in both Lambda functions. This will reduce the size of the Lambda deployment packages and avoid reaching the quota for the maximum size of zipped deployment packages. The developer can also benefit from using layers to manage dependencies separately from function code.

References:

? [What Is AWS Lambda? - AWS Lambda]

? [AWS Lambda Layers - AWS Lambda]

#### NEW QUESTION 138

A developer wants to deploy a new version of an AWS Elastic Beanstalk application. During deployment, the application must maintain full capacity and avoid service interruption. Additionally, the developer must minimize the cost of additional resources that support the deployment.

Which deployment method should the developer use to meet these requirements?

A.

- B. Rolling with additional batch
- C. Blue/green
- D. Immutable

**Answer:** D

**Explanation:**

The immutable deployment method is the best option for this scenario, because it meets the requirements of maintaining full capacity, avoiding service interruption, and minimizing the cost of additional resources.

The immutable deployment method creates a new set of instances in a separate Auto Scaling group and deploys the new version of the application to them. Then, it swaps the new instances with the old ones and terminates the old instances. This way, the application maintains full capacity during the deployment and avoids any downtime. The cost of additional resources is also minimized, because the new instances are only created for a short time and then replaced by the old ones. The other deployment methods do not meet all the requirements:

? The all at once method deploys the new version to all instances simultaneously, which causes a short period of downtime and reduced capacity.

? The rolling with additional batch method deploys the new version in batches, but for the first batch it creates new instances instead of using the existing ones. This increases the cost of additional resources and reduces the capacity of the original environment.

? The blue/green method creates a new environment with a new set of instances and deploys the new version to them. Then, it swaps the URLs between the old and new environments. This method maintains full capacity and avoids service interruption, but it also increases the cost of additional resources significantly, because it duplicates the entire environment.

**NEW QUESTION 139**

A developer is creating a serverless application that uses an AWS Lambda function. The developer will use AWS CloudFormation to deploy the application. The application will write logs to Amazon CloudWatch Logs. The developer has created a log group in a CloudFormation template for the application to use. The developer needs to modify the CloudFormation template to make the name of the log group available to the application at runtime. Which solution will meet this requirement?

- A. Use the AWS::Include transform in CloudFormation to provide the log group's name to the application.
- B. Pass the log group's name to the application in the user data section of the CloudFormation template.
- C. Use the CloudFormation template's Mappings section to specify the log group's name for the application.
- D. Pass the log group's Amazon Resource Name (ARN) as an environment variable to the Lambda function.

**Answer:** D

**Explanation:**

FunctionName: MyLambdaFunction Code:

S3Bucket: your-lambda-code-bucket S3Key: lambda-code.zip

Runtime: nodejs14.x # Specify the desired runtime for your Lambda function Environment:

Variables:

LOG\_GROUP\_NAME: !Ref MyLogGroup <https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/aws-resource-logs-loggroup.html>

**NEW QUESTION 140**

A developer is building an application that gives users the ability to view bank account from multiple sources in a single dashboard. The developer has automated the process to retrieve API credentials for these sources. The process invokes an AWS Lambda function that is associated with an AWS CloudFormation custom resource.

The developer wants a solution that will store the API credentials with minimal operational overhead.

Which solution will meet these requirements?

- A. Add an AWS Secrets Manager GenerateSecretString resource to the CloudFormation template.
- B. Set the value to reference new credentials to the CloudFormation resource.
- C. Use the AWS SDK ssm PutParameter operation in the Lambda function from the existing, custom resource to store the credentials as a parameter.
- D. Set the parameter value to reference the new credential.
- E. Set the parameter type to SecureString.
- F. Add an AWS Systems Manager Parameter Store resource to the CloudFormation template.
- G. Set the CloudFormation resource value to reference the new credentials. Set the resource NoEcho attribute to true.
- H. Use the AWS SDK ssm PutParameter operation in the Lambda function from the existing custom resources to store the credentials as a parameter.
- I. Set the parameter value to reference the new credential.
- J. Set the parameter NoEcho attribute to true.

**Answer:** B

**Explanation:**

The solution that will meet the requirements is to use the AWS SDK ssm PutParameter operation in the Lambda function from the existing custom resource to store the credentials as a parameter. Set the parameter value to reference the new credentials. Set the parameter type to SecureString. This way, the developer can store the API credentials with minimal operational overhead, as AWS Systems Manager Parameter Store provides secure and scalable storage for configuration data. The SecureString parameter type encrypts the parameter value with AWS Key Management Service (AWS KMS). The other options either involve adding additional resources to the CloudFormation template, which increases complexity and cost, or do not encrypt the parameter value, which reduces security.

Reference: Creating Systems Manager parameters

**NEW QUESTION 142**

A developer is troubleshooting an application in an integration environment. In the application, an Amazon Simple Queue Service (Amazon SQS) queue consumes messages and then an AWS Lambda function processes the messages. The Lambda function transforms the messages and makes an API call to a third-party service.

There has been an increase in application usage. The third-party API frequently returns an HTTP 429 Too Many Requests error message. The error message prevents a significant number of messages from being processed successfully.

How can the developer resolve this issue?

- A. Increase the SQS event source's batch size setting.
- B. Configure provisioned concurrency for the Lambda function based on the third-party API's documented rate limits.
- C. Increase the retry attempts and maximum event age in the Lambda function's asynchronous configuration.
- D. Configure maximum concurrency on the SQS event source based on the third-party service's documented rate limits.

**Answer:** D

**Explanation:**

? Maximum concurrency for SQS as an event source allows customers to control the maximum concurrent invokes by the SQS event source<sup>1</sup>. When multiple SQS event sources are configured to a function, customers can control the maximum concurrent invokes of individual SQS event source<sup>1</sup>.

? In this scenario, the developer needs to resolve the issue of the third-party API frequently returning an HTTP 429 Too Many Requests error message, which prevents a significant number of messages from being processed successfully. To achieve this, the developer can follow these steps:

? By using this solution, the developer can reduce the frequency of HTTP 429 errors and improve the message processing success rate. The developer can also avoid throttling or blocking by the third-party API.

**NEW QUESTION 146**

.....

## THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual AWS-Certified-Developer-Associate Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the AWS-Certified-Developer-Associate Product From:

<https://www.2passeasy.com/dumps/AWS-Certified-Developer-Associate/>

## Money Back Guarantee

### **AWS-Certified-Developer-Associate Practice Exam Features:**

- \* AWS-Certified-Developer-Associate Questions and Answers Updated Frequently
- \* AWS-Certified-Developer-Associate Practice Questions Verified by Expert Senior Certified Staff
- \* AWS-Certified-Developer-Associate Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- \* AWS-Certified-Developer-Associate Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year